



## Pro-MSP™

Pro-MSP™ is an MS-Polymer adhesive that is exceptionally easy to clean off of pre-finished hardwood, before or even after cure. Pro-MSP™ offers moisture vapor protection for engineered hardwood up to 15 lbs per 1,000 square feet per 24 hours, or 87% RH. Protect against the hassle and cost of difficult clean up by using Bostik's Pro-MSP™.

### Product Features

- Adhesive and moisture membrane all in one
- Easy to spread
- Low odor & VOC
- Easy clean before and after cure
- Bonds tenaciously to concrete and flooring, but not finish
- Low moisture vapor permeability
- Bridges cracks up to 1/8"
- May contribute to LEED® credits
- Versatile: use to glue down engineered, solid, bamboo, cork and parquet flooring

### APPLICATION PROPERTIES

Application Method	Trowel	
Ease of Application	Easy	
Odor	Slight	
Required Flash Time	0 min	
Open/Working Time*	60 min	
Color	Brown	
Density (lbs/gallon)	15.44	
Wet Lay	Yes	
Walk-On-Work prior to cure	No	
Percent of Adhesive Coverage & Transfer Required	Moisture Protection	Bond Only
	Engineered	>80%
Solid	100%	>95%
Application Temp Range	50°F-90°F (10°C-32°C)	
Shelf Life	1 year	
Ease of Clean, Wet	Very Easy	
Ease of Clean, cured on pre-finished hardwood	Easy	

\*Under normal working conditions

For more information, contact us at:

1-800-726-7845 | [www.bostik.com/us](http://www.bostik.com/us)

T3074\_05.26.20

