



Sovereign FungiChek AntiCon

ADVANCED ANTI-MOULD EMULSION PAINT WHICH REDUCES SURFACE CONDENSATION

TECHNICAL SHEET NO: TDS02259 22/08/2025

SMART ADVANTAGES

- Reduces the effects of condensation
- Resistant to black mould
- Ideal for kitchens, bathrooms and utility rooms

DESCRIPTION

Sovereign FungiChek AntiCon is a ready-to-use advanced mould-resistant emulsion paint which reduces surface condensation. Sovereign FungiChek AntiCon can be used on internal walls, ceilings, pipework and metals to provide protection from fungi and mould growth. It is ideal for use on walls & ceilings in kitchens, bathrooms & utility rooms, any cold spots, or anywhere condensation and mould could be and/or are a problem.

Sovereign FungiChek AntiCon uses proven FungiChek technology to inhibit mould growth whilst also reducing surface condensation. It does this with the use of glass nanospheres. These are tiny glass bubbles of air that reduce heat loss from the surface and therefore increase the dew point – the temperature at which water vapour turns into water droplets. Sovereign FungiChek AntiCon also contains diatoms – these are hollow shells of mineral that can absorb moisture, preventing liquid water forming on the surface of the paint. It is then released back into the atmosphere as vapour when conditions allow. Sovereign FungiChek AntiCon makes walls warmer to the touch. It is available as a fine texture emulsion in white and magnolia.



TECHNICAL CHARACTERISTICS

Colour	White & magnolia
Form	Viscous liquid
Specific gravity	1.02 approx.
Composition	Acrylic emulsion
Application temperature	+5°C to +25°C
Drying time	Single coat at normal thickness: up to 4 hours before re-coating. (depending on coating thickness, ambient temperature and humidity)
HSE number	6476-GB (amateur & professional use)

COVERAGE

- 8 to 10m² per litre
- Extra allowances should be made for particularly coarse or porous surfaces.
(depending on substrate texture, porosity & application technique)

APPLICATION

IMPORTANT: Before using Sovereign FungiChek AntiCon, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Prepare surfaces by removing non-washable and loose material e.g., distemper, grease, dirt, mould or wallpaper.
- Sovereign DentoLite Sterilising Solution can be used to soak wallpaper before removal to minimise spread of mould spores and any further mould infection.
- Make good any surface defects and rub down to a smooth finish.
- Wash down with Sovereign DentoLite Sterilising Solution using a cloth. Allow to dry thoroughly. Apply second wash in badly affected areas and allow to dry completely.
- Treat all bare areas with an appropriate primer or undercoat/sealer.
- If the surface is chalky or friable, apply a liberal coat of Bostik Stabilising Solution.

APPLICATION

- Stir thoroughly before use.
- Sovereign FungiChek AntiCon may be applied by brush or roller. Protect any adjacent surfaces.
- Prepare surfaces as described above.
- Apply at least two coats Sovereign FungiChek AntiCon, allowing sufficient drying time between coats (2 to 4 hours).
- The more coats that are applied, the better the protection from condensation.
- Apply each coat more thickly than you would normal emulsion as this will improve performance.
- **IMPORTANT:** Do not overcoat with other materials. Overcoating Sovereign FungiChek AntiCon with a normal paint coating will allow the re-growth of black mould, as the fungicides and diatoms will no longer be at the surface.

GENERAL CONDENSATION ADVICE

There are basic measures to assist in the control of condensation and black mould. Sovereign products complement these basic controls and can prevent these problems occurring for many years.

These methods are particularly helpful in the domestic environment but can also be applied to commercial or leisure establishments.

It is always important to reduce the risk of condensation by observing the following simple recommendations:

- Ensure rooms are sufficiently warm and properly ventilated.
- Improve internal/external wall insulation.
- Attempt to maintain a balance between ventilation, heating and insulation.
- When cooking, washing, bathing or drying clothes, keep doors closed, windows open and extraction fans running - this prevents warm, moist air moving to colder areas of the building.
- Do not dry clothes on radiators. Tumble dryers must be vented externally, unless of the condensing type.
- Fit ventilation units, where required, such as Sovereign Passive Vapour Vents, Sovereign Auto ConCure Positive Input Ventilation Systems and/or Sovereign Extract Fans.

- If a paraffin or flueless gas heater is used, ensure a window is open a little (every litre of paraffin produces about 1 litre of water).
- Use dehumidifiers, where appropriate.

CLEANING

- Clean tools and equipment with water immediately after use. Immediately remove spills and splashes.

STORAGE

- Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

Internal use only.

The colour indicated on pack is a guide only. It is recommended that users apply a small amount of Sovereign FungiChek AntiCon in an inconspicuous area and allow to dry to determine colour suitability before commencing work. Shade variations may occur between batches. When completing projects requiring multiple cans, please ensure that they are from the same batch.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Sovereign FungiChek AntiCon, available at www.bostik.com/uk.

PACKAGING

Product codes	30605598	White 5L can x 2
	30605512	Magnolia 5L can x 2

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone:	01785 272625
Sales:	customer.service@bostik.com
Technical advice:	technical.service@bostik.com
Safety data sheets:	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.