



BOSTIK

BUTYL 1590 BLACK

BUTYL 1590 BLACK IS A THERMOPLASTIC HOT MELT BUTYL

SMART ADVANTAGES

- High sealing performance
- Room temperature applied
- Application on non cleaned surface or oily material

PRODUCT DESCRIPTION

An air drying butyl based elastic sealant with especially good adhesion to metal surfaces. At room temperature the joint surface is tack free after a couple of hours. The cured mastic has a soft rubber-like consistency.

RECOMMENDED USE

Specially designed for sealing of joints in plate constructions such as car door sealing, ventilation canals, fan rooms, caravans etc with high demands on tightness. Good adhesion to metal, but also glass, stone, plastic, wood etc.

METHOD OF USE

The product can be use on non cleaned surface; however, to get the best adhesion possible, surfaces shall be dry, clean and free from loose particles. To remove grease, acetone can be used. The product is applied with hand- or compressed air gun.

IMPORTANT

The product is flammable and dangerous. Use effective ventilation or use breathing apparatus type A2. For further information, please see material safety data sheet

TECHNICAL DATA

| | | |
|----------------------------|-------------------|--|
| Color | | Grey or Black |
| Density | g/cm ³ | About 1.35 |
| Solids Content | % | 80 |
| Solvent | | White Spirit |
| Type | | Butyl compound |
| Consistency | | Flexible gunable compound |
| Working Temperature | °C | Not below +5 |
| Flammable | | Yes. (Dry compound is non- flammable.) |
| Paintability | | Yes |
| Drying | | Successively, but maintains some activity on surface |

DISCLAIMER

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.