



Den Braven

Elast-O-Rub

A versatile non filled sealant



PRODUCT DESCRIPTION

Zwaluw Elast-O-Rub is a versatile non filled sealant based on Styrol-Blokcopolymer (S-EB-S) which cures by evaporation of solvents to a soft plastic elastic rubber.

KEY BENEFITS

Adheres to most, even damp, surfaces
Paintable with most water based and synthetic paints

APPLICATIONS

Zwaluw Elast-O-Rub was developed for temporary repairs of joints and cracks between stone, concrete and metal. Also suitable for repairing leaks in gutters and other water proofings.

TECHNICAL SPECIFICATIONS

100% Modulus		0,5 (N/mm2)
Application Temperature		+5°C to +40°C
Base		Synthetic rubber
Density		0,95 g/ml
Shore A Hardness	DIN 53505	25 ± 5
Skin Formation		3-5 minutes (@ +23°C/50% RH)
Temperature Resistance		-25°C to +100°C
Shrinkage		approximately 20%

These are typical values

LIMITATIONS

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

SURFACE PREPARATIONS AND FINISHING

Application temperature: +5°C to +40°C (applies to environment and substrates). All substrates must be solid, clean and free of grease and dust. Clean substrates with Zwaluw Cleaner. Zwaluw Elast-O-Rub adheres perfectly without the use of primer to most non porous substrates. Always test adhesion prior to application.

CLEANING

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life till 24 months after date of production, stored in a dry place.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.