

Technical Data Sheet

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC OVER PAINTABLE IMMEDIATELY AFTER APPLICATION



PRODUCT DESCRIPTION

A high quality acrylic sealant specifically developed to be overpainted with water based and synthetic paints immediately after application. This product is for interior use and adheres to most surfaces perfectly without the use of a primer. This product has low odour, does not discolour, is easy to apply and not corrosive towards metals.

KEY BENEFITS

- Paintable immediately after application with water based and synthetic paints
- Reduces cracking and discolouration of the paint
- Perfect adhesion without the use of a primer to most substrates
- Nearly odourless
- Easy to apply and clean
- Non corrosive towards metals

APPLICATIONS

For the sealing and filling of gaps and cracks where movement can occur, such as those between plasterwork and window frames, door frames, skirting boards, windowsills and architraves. For filling cracks and screw and nail holes in walls and ceilings. Use prior to painting and wall papering to prevent unsightly cracks developing later. Has good adhesion without primer on concrete, brickwork, plaster and painted wood.

DIRECTION FOR USE

Cut the cartridge seal and screw on the nozzle which should be cut to the required size. Using a skeleton gun,

apply the sealant into the gap or joint ensuring a good solid fill. If required, place masking tape along edges removing within 5 minutes of application.

TECHNICAL SPECIFICATIONS

100% Modulus	DIN 53504 S2	0,52 N/mm ²
Application Temperature		+5°C to +40°C
Base		Acrylic dispersion
Application Rate	@ Ø3 mm/4 bar	100 g/min
Curing Time	@ +23°C/50% RH	1 mm/24 hours
Density	ISO 1183-1	0,71 g/ml
Elongation At Break	DIN 53505/ ISO 868	132%
Fire Rating		Class E
Flow	ISO 7390	1 mm
Frost Resistance		Up to -15°C
Shore A Hardness	DIN 53505 / ISO 868	33
Skin Formation	@+23°C/50% RH (DBTM 16)	2 minutes
Temperature Resistance		-20°C to +75°C
Tensile Strength	DIN 53504	0,52

SURFACE PREPARATIONS AND FINISHING

Surfaces must be clean and solid. Use diluted product as a primer for highly porous surfaces. Adhesion tests prior to application are recommended. Always tool using a spatula or stick wetted with water within 5 minutes of application. Uncured sealant can be removed with water.

PAINTABILITY

Paintable immediately after application with water based and synthetic paints providing a skin has formed. In excessive joint movements cracking can occur. We recommend a paint compatability test prior to application.

CLEANING

Tools to be cleaned after use with water. Hands can be cleaned with Multi-Purpose Cleaning Wipes.

PACKAGING DESCRIPTION


For product specifications, please refer to the Product Detail Page

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life till 12 months after production date, stored in a dry place.

BOSTIK CERTIFICATIONS

- A+ French VOC Regulation
- Emission EC1 Plus
- EN 15651-1: F-INT
- M1



HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

LIMITED WARRANTY

Siroflex warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

