Den Braven

Mixed Finisher Spray

Joint sealant finishing additive



PRODUCT DESCRIPTION

Zwaluw Mixed Finisher is a ready mixed neutral universal additive for the wet tooling of sealants in joints. Zwaluw Mixed Finisher is more than 99% Biodegradable.

KEY BENEFITS

Ready to use
Pre mixed to the correct ratio
99% Biodegradable

APPLICATIONS

Zwaluw Mixed Finisher was developed for the wet tooling of sealants in joints. Before use always mix thoroughly. After application of the sealants the surface of the joints and the neighbouring surfaces must be moistened with Zwaluw Mixed Finisher Spray. The joint may be tooled using a spatula, a putty knife or PVC pipe. After smoothing the joint can be finished with a finger dipped in Zwaluw Mixed Finisher Spray.

TECHNICAL SPECIFICATIONS

Application Temperature	+5°C to +40°C
Density	1,00 g/ml
Frost Resistance	Up to -15°C
pH-value	7.1

These are typical values

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life till 24 months after production date, stored in a dry place.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

"Arkema Middle East DMCC
Unit 1108 JBC 3 Tower, Cluster Y, Jumeirah
Lakes Towers, P.O. Box 336393 Dubai
T +971 48751704 | E
bostik.mena-info@bostik.com"