



Den Braven

Plasterboard-Filler

Ultra lightweight ready to use filler



PRODUCT DESCRIPTION

Zwaluw Plasterboard-Filler is virtually a non shrinking, ready to use ultra light, ready mixed filler and spackling compound for filling and repairing cracks and holes in walls and ceilings.

KEY BENEFITS

- Ultra lightweight
- Almost non-shrinking
- Paintable with water based- and synthetic paints
- Sandable after curing
- Easy to apply and clean
- Non corrosive towards metals

APPLICATIONS

Zwaluw Plasterboard-Filler was specifically developed for filling one time joints and screw holes in plasterboard walls and ceilings for interior applications. Also for one time filling, repairing and smoothing of holes and cracks in concrete, plaster, brickwork and stucco layers.

DIRECTION FOR USE

For best results, the product should be applied without pressure.

TECHNICAL SPECIFICATIONS

Application Temperature		+5°C to +30°C
Base		Acrylic dispersion
Density		0,60 g/ml
Flow	ISO 7390	< 2 mm
Frost Resistance		Up to -15°C
Skin Formation	DBTM 16 (internal test method)	5 minutes @ +23°C/50% RH
Temperature Resistance		-20°C to +75°C
Shrinkage		<5%

These are typical values

LIMITATIONS

Not suitable for continuous exposure to water, Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

SURFACE PREPARATIONS AND FINISHING

Application temperature +5°C to +30°C (applies to environment and substrate). All surfaces must be solid, clean, free of dust and grease. Substrates to be cleared of all loose particles, porous substrate do not need to be dry. Very porous substrates like: gypsum, airated concrete, limestone, etc, need to be primed with a mixture of 1 part Zwaluw Plasterboard-Filler and 2 parts water. Adhesion tests prior to application are recommended. Finish and smooth with a wet spatula.

PAINTABILITY

Zwaluw Plasterboard-Filler is paintable when fully dry. During curing product will show minimal shrinkage, which can cause cracking of the paint. Paintable with water based and synthetic paints. Painting with highly water based paints can create cracking. We recommend testing compatability with paint prior to application.

CLEANING

Tools to be cleaned after use with water. Hands can be cleaned with Zwaluw Wipes and/or water and soap.

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life till 12 months after production date, stored in a dry place.

BOSTIK CERTIFICATIONS

- EN 13963: 1A
- Emission EC1 Plus
- M1



HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.