

Technical Data Sheet

SX MIGHTY STRENGTH MITRE BOND HIGH STRENGTH BONDING SYSTEM KIT FOR USE IN THE TRADE



PRODUCT DESCRIPTION

A high strength bonding system kit for use in the trade. SX Mitre Bond Activator accelerates the curing speed of SX Mitre Bond Superglue, particularly on porous, acidic or difficult to bond surfaces, or when ambient temperatures are low.

KEY BENEFITS

- High strength bonding system kit for use in the trade

APPLICATIONS

Ideal for bonding wood mitre joints, rubbers, plastics and ceramics.

DIRECTION FOR USE

Apply the SX Mitre Bond Activator before applying the SX Mitre Bond Superglue. Shake can well before use. Holding the can approximately 20 cm away, spray onto one of the surfaces to be bonded for no longer than one second. Allow solvent to evaporate. Apply SX Mitre Bond Superglue to the other surface and assemble parts accurately holding for approximately 10 seconds. Bond will be instant.

TECHNICAL SPECIFICATIONS

Base	SX Mitre Bond Superglue - Ethyl Cyanoacrylate
Curing Time	Very fast, usually < 10 secs

SURFACE PREPARATIONS AND FINISHING

Surfaces to be bonded must be clean, dry and free from grease. Adhesion and patch tests on a hidden area prior to application are recommended.

PACKAGING DESCRIPTION

For product specifications, please refer to the Product Detail Page

SHELF LIFE

Shelflife of 12 months after production date stored in original, unopened packaging between +2°C and +25°C, in cool, dry conditions.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

LIMITED WARRANTY

Siroflex warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any

liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

