

Technical Data Sheet

SX CONTRACTORS PVCU SILICONE LOW MODULUS NEUTRAL CURE SILICONE



PRODUCT DESCRIPTION

A fast, neutral curing silicone specifically formulated for use on most PVCu. It is UV, water and moisture resistant and almost odourless. Cures with atmospheric moisture to form a durable rubber seal.

KEY BENEFITS

- UV, water and moisture resistant
- Almost odourless

APPLICATIONS

Sealing connection and movement joints in building constructions. Ideal for perimeter pointing of window and door frames, sealing plastic roof-line areas and general weather sealing.

DIRECTION FOR USE

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the sealant into the gap or joint ensuring a good solid fill. If required place masking tape along edges, removing within 5 minutes of application. In deep joints reduce the joint depth to 50% of the joint width using expanding foam or joint backer rod.

TECHNICAL SPECIFICATIONS

LIMITATIONS

- Not suitable for PE, PP, PTFE, neoprene and bituminous surfaces
- Not suitable for insulation or laminated glass

SURFACE PREPARATIONS AND FINISHING

Surfaces must be clean, dry and free from dust, grease and other loose material. Adhesion tests prior to application are recommended. Always tool using a stick or spatula wetted with neutral soapy water within 5 minutes of application.

PAINTABILITY

This product is not paintable.

PACKAGING DESCRIPTION

For product specifications, please refer to the Product Detail Page

SHELF LIFE

Shelflife of 12 months after production date. Store in unopened, original packaging between +5°C and +25°C in cool, dry conditions

BOSTIK CERTIFICATIONS

- ISEGA

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

LIMITED WARRANTY

Siroflex warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors,

incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

