

Siroflex
Quality Performance Products

Technical Data Sheet

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC

FLEXIBLE SEALANT TO GIVE A PROFESSIONAL FINISH



PRODUCT DESCRIPTION

A premium grade, flexible sealant that is easy to apply, dries quickly and can be over painted with most water based and synthetic paints. For interior and exterior* use. Adheres without primer to most substrates. It is almost odour free and is not corrosive towards metals.

KEY BENEFITS

- Paintable with water based and synthetic paints
- Perfect adhesion without primer to most substrates
- Interior and exterior use
- Nearly odourless
- Easy to apply
- Easy to clean
- Non corrosive towards metals

APPLICATIONS

For the sealing and filling of gaps and cracks where movement can occur, such as those between plasterwork, perimeter sealing of window and door frames, skirting boards and architraves. Use prior to painting or wall papering to fill cracks to give a professional finish.

DIRECTION FOR USE

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the sealant into the gap or joint ensuring a good solid fill. If required, place masking tape along edges, removing within 5 minutes of application. Smooth off whilst wet, do not attempt to abrade when cured.

TECHNICAL SPECIFICATIONS

100% Modulus	DIN 53504 S2	0,3 N/mm²
Application Temperature		+5°C to +40°C
Base		Acrylic dispersion
Application Rate	@ Ø3 mm/4 bar	450 g/min
Curing Time		
Density		1,71 g/ml
Elongation At Break		200%
Flow	ISO 7390	< 2mm
Frost Resistance		Up to -15°C
Joint Movement		7,5%
Shore A Hardness	DIN 53505/ ISO 868	30
Skin Formation	DBTM 16 (internal test method)	5 minutes @+23°C/50% RH
Temperature Resistance		-20°C to +75°C
Tensile Strength		0,3 N/mm²

LIMITATIONS

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

SURFACE PREPARATIONS AND FINISHING

Surfaces must be clean and solid. Adhesion tests prior to application are recommended. Always tool using a spatula or stick wetted with water within 5 minutes of application. Uncured sealant can be removed with water.

PAINTABILITY

Can be over painted with most water based and synthetic paints when sealant is fully cured. Painting over with highly filled water based paints can cause cracks in the paint film. We recommend a paint compatability test before application.

CLEANING

Tools to be cleaned after use with water. Hands can be cleaned with Multi-Purpose Cleaning Wipes and/or water and soap.

Den Braven
Siroflex Limited
Dodworth Business Park, S75 3SP Barnsley, South Yorkshire
T +44 (0) 1226771600 | E info@siroflex.co.uk

PACKAGING DESCRIPTION

For product specifications, please refer to the Product Detail Page

COLOR

White

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life till 18 months after production date, stored in a dry place.

CERTIFICATIONS

- EN 15651-1: F-EXT-INT 7.5P
- A+ French VOC Regulation
- Emicode EC1 Plus – very low emission

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Siroflex warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

Den Braven
Siroflex Limited
Dodworth Business Park, S75 3SP Barnsley, South Yorkshire
T +44 (0) 1226771600 | E info@siroflex.co.uk