



Den Braven

Tixoplast®

1-component bitumen based sealant



PRODUCT DESCRIPTION

Zwaluw Tixoplast® is a 1-component bitumen based sealant which cures to a plastic seal by evaporation of the solvent.

APPLICATIONS

Zwaluw Tixoplast® was developed as an adhesive for bituminous roofing and insulation panels (not of polystyrene), weatherproof sealing of joints, eaves, gutters, skylights, chimneys, etc. Zwaluw Tixoplast® can also be used as sealing for leaks, emergency repairs even in wet weather. Also for filling of cracks, joints and blisters on roofs and gutters in roofing, zinc and to adhere shingles to sloped roofs.

TECHNICAL SPECIFICATIONS

Application Temperature	+5°C to +40°C
Base	Bitumen
Density	1,30 g/ml
Frost Resistance	Up to -15°C
Temperature Resistance	-20°C to +70°C

These are typical values

LIMITATIONS

Not suitable for PE, PP, PC, PMMA and PTFE

SURFACE PREPARATIONS AND FINISHING

Application temperature +5°C to +40°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Clean substrates with Zwaluw Cleaner. Substrates to be free of dust and loose particles. Non-porous substrates do not need to be absolutely dry. Always test adhesion prior to application.

CLEANING

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life till 9 months after production date, stored in a dry place.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.