

Technical Data Sheet

TRADE SKELETON GUN TRADE SKELETON CAULKING GUN



PRODUCT DESCRIPTION

A single component manual bead gun applicator ideal for DIY and semi-professional users. Strong rigid metal frame with curved rod end (ladder hook) for convenient storage and built-in pressure relief device to stop material flow when trigger is released.

KEY BENEFITS

- Mechanical Advantage (ratio): 7:1
- Barrel Length: 267.8 mm
- Maximum Force (plunger): 1.2kN
- Tool Weight: 0.54kg
- Tool Material: Epoxy coated steel, epoxy coated steel cradle
- Certificates: ISO 9001:2008, REACH

APPLICATIONS

Designed for use with 310ml and 400ml cartridges of low viscosity sealants and adhesives.

DIRECTION FOR USE

Keep all tools out of the reach of children.

CLEANING

Issue 1/29.04.16

PACKAGING DESCRIPTION

For product specifications, please refer to the Product Detail Page

COLOUR

Orange

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

LIMITED WARRANTY

Siroflex warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.