



Sovereign DeepKill

TIMBER PRESERVATION CREAM

TECHNICAL SHEET NO: TDS02269 25/10/2024

SMART ADVANTAGES

- Eradicates & protects against fungi and wood boring insects
- For softwoods & hardwoods
- Can be over painted

DESCRIPTION

Sovereign DeepKill is a deep penetrating, timber treatment cream to eradicate and protect against all types of wood boring insects such as common furniture beetle & deathwatch beetle and wood destroying fungi such as dry rot (serpula lacrymans) & wet rot. It can be used as a curative system when an attack is active, or as a preventative measure to guard against future outbreaks.

It is easy to apply by brush or roller and is non-drip. It can be used on all types of softwood and hardwood, including floorboards, roofing timbers and furniture. It is particularly useful for thick sectioned timber such as floor joists and roof supports.

The cream penetrates the timber, carrying the active fungicides and insecticides deep below the surface, quickly eliminating existing attacks and preserving the timber. Once dry, the timber returns to its original colour and will accept decorative coatings such as paint and varnish as normal.

On application of the paste, a skin is formed which prevents evaporation of the carrier solvent, maximising the uptake of active material into the timber. When applied at the correct coverage rates, on drying, no residue will remain. For professional use only.



TECHNICAL CHARACTERISTICS

Colour	White
Form	Paste
Specific gravity	0.84 approx.
Composition	Mixture of active ingredients
Application temperature	+5°C to +25°C
Drying time	Touch: 6 to 8 hours Full: 24 hours (depending on coating thickness, ambient temperature and humidity)
HSE No.	10149-GB

COVERAGE

- Approx. 4m² per litre
(depending on substrate and application technique)

APPLICATION

IMPORTANT: Before using Sovereign DeepKill, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

Restricted to professional users.

PREPARATION

- Ensure timber is free from any dirt or debris and that coatings such as paint and varnish have been removed.

APPLICATION

- Apply by brush or roller to clean, dry, bare timber (no coatings), at a rate of 250ml per square metre. Ensure an even coverage.
- Coated timber can be treated by drilling 10mm diameter holes and filling them with Sovereign DeepKill.
- When injecting into holes, apply at a rate of 30kg per metre cubed.
- When drilling, ensure that the structural integrity of the timber is not affected.
- Care should be taken to prevent contamination of adjacent plaster.
- If required, once treated and dry, the timber is ready to receive decorative coatings such as paints and stains as on drying no residue will remain.
- No further maintenance regime is required after application. However, general building maintenance is required to prevent water ingress.

CLEANING

- Clean tools and equipment with soapy water or white spirit immediately after use.

STORAGE

- Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 2 years from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Sovereign DeepKill, available at www.bostik.com/uk.

PACKAGING

Product codes	30609023	5L buckets
----------------------	----------	------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625
Sales: customer.service@bostik.com
Technical advice: technical.service@bostik.com
Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.