



SUBSTRATE ADHESIVE COMPATIBILITY

TILING. BY BOSTIK

RESIDENTIAL															
	INTERIOR										EXTERIOR				
	BATHROOMS		KITCHENS		INTERIOR		LIVING AREAS	FOYERS	UNDE FLOOR HEATING	LARGE FORMAT	EXTERIOR WALLS	FEATURE WALLS	BALCONIES	POOLS	PATIOS/ OUTDOOR ENTERTAINING
	FLOORS	WALLS	FLOORS	WALLS	FLOORS	WALLS									
PLASTER		Megafix		Megafix		Megafix	Evoflex	Evoflex	Evoflex	Evoflex	Ultra Mastik	Ultra Mastik			
CONCRETE	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Evoflex	Evoflex	Evoflex	Ultra Mastik	Ultra Mastik		Ultra Mastik + Megalastic	
HEATED CONCRETE	Evoflex		Evoflex		Evoflex		Evoflex	Evoflex	Evoflex	Evoflex	Ultra Mastik	Ultra Mastik			
SAND/CEMENT SCREED	Evoflex		Evoflex		Evoflex		Evoflex	Evoflex	Evoflex	Evoflex					
TILES	Evoflex + primer	(tile on tiles on wall not permitted)	Evoflex + primer	(tile on tiles on wall not permitted)	Evoflex + primer	(tile on tiles on wall not permitted)	Evoflex + primer	Evoflex + primer	Evoflex + primer	Evoflex	(tile on tiles on wall not permitted)	(tile on tiles on wall not permitted)	Evoflex + primer	Ultra Mastik + Megalastic	Asaflex
FIBRE-CEMENT (6mm)	Conflex	Megafix	Conflex	Megafix	Conflex	Megafix	Conflex	Conflex	Ultra Mastik	Evoflex	Ultra Mastik	Ultra Mastik	Evoflex		Evoflex
SCYON COMPRESSED SHEET (19mm)	Conflex		Conflex		Conflex		Conflex	Conflex	Conflex	Evoflex	Ultra Mastik	Ultra Mastik	Evoflex		Evoflex
TIMBER	Asaflex		Asaflex		Asaflex		Asaflex	Asaflex	Asaflex	Asaflex			Asaflex		Asaflex
AKRIL SHOWERBASES	(direct tiling not permitted); apply Dampfix Gold then Ultra mastik	(direct tiling not permitted); apply Dampfix Gold then Ultra mastik													
RENDER	Ultra Mastik	Megafix	Ultra Mastik	Megafix	Ultra Mastik	Megafix	Ultra Mastik	Ultra Mastik	Ultra Mastik	Ultra Mastik	Ultra Mastik	Ultra Mastik	Evoflex	Ultra Mastik + Megalastic	Ultra Mastik
DAMPFIX GOLD	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Evoflex	Evoflex	Evoflex	Ultra Mastik	Ultra Mastik	Evoflex	Use Dampfix Immersed for pools	Evoflex

COMMERCIAL																			
	INTERIOR												EXTERIOR						
	BATHROOMS		WETROOMS		COMMERCIAL KITCHENS		LAUNDRY		LARGE FORMAT		SHOW ROOMS	HEALTH CARE	EDUCATION	RETAIL	BALCONIES	DRIVEWAYS	POOLS	ENTERTAINING	
	FLOORS	WALLS	FLOORS	WALLS	FLOORS	WALLS	FLOORS	WALLS	FLOORS	WALLS									
PLASTER		Megafix		Megafix				Megafix										Evoflex	
CONCRETE	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Evoflex	Evoflex	Evoflex	Evoflex	Evoflex	Evoflex	Ultra Mastik + Megalastic	Evoflex
HEATED CONCRETE	Evoflex		Evoflex		Evoflex	Ultra Mastik	Evoflex		Evoflex	Ultra Mastik	Evoflex	Evoflex	Evoflex	Evoflex	Evoflex			Evoflex	
SAND/CEMENT SCREED	Evoflex		Evoflex		Evoflex		Evoflex		Evoflex		Evoflex	Evoflex	Evoflex	Evoflex	Evoflex	Evoflex		Ultra Mastik + Megalastic	Evoflex
FIBRE-CEMENT (6mm)	Conflex	Megafix	Conflex	Megafix	Conflex	Ultra Mastik	Conflex	Megafix	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Ultra Mastik	Ultra Mastik	Evoflex				Evoflex
SCYON COMPRESSED SHEET (19mm)	Conflex		Conflex		Evoflex		Conflex		Evoflex	Evoflex	Evoflex	Evoflex	Evoflex	Evoflex	Evoflex				Evoflex
TIMBER	Asaflex		Asaflex		Asaflex		Asaflex		Asaflex		Asaflex	Asaflex	Asaflex	Asaflex					Asaflex
AKRIL SHOWERBASES	(direct tiling not permitted); apply Dampfix Gold then Ultra Mastik	(direct tiling not permitted); apply Dampfix Gold then Ultra Mastik																	
RENDER	Ultra Mastik	Megafix	Ultra Mastik	Megafix	Ultra Mastik	Ultra Mastik	Ultra Mastik	Megafix	Evoflex	Ultra Mastik	Ultra Mastik	Ultra Mastik	Ultra Mastik	Ultra Mastik	Ultra Mastik			Ultra Mastik + Megalastic	Ultra Mastik
DAMPFIX GOLD	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Ultra Mastik	Evoflex	Evoflex	Evoflex	Evoflex	Evoflex			Use Dampfix Immersed for pools	Evoflex

This is not a definitive list, nor does it supersede recommendations in the Technical Data Sheets or from Bostik technical staff.

If there is any doubt about substrate suitability or preparation, contact Bostik Technical Services before commencing work.

Consult Technical Data Sheet from Bostik website for current and accurate application information. Commencement of system installation shall be taken as acceptance of the substrate suitability and preparation by the applicator.

SMART HELP: 1800 267 845