



# P925

## FOAM'N'FIX TURBO MULTI-USE FAST TACK AND QUICK SETTING UNIVERSAL FOAM ADHESIVE

### TECHNICAL DATA SHEET

#### BENEFITS

- Fast curing and quick setting foam adhesive
- Maximum open time of 2.5 minutes
- Saves time & money
- High shear and tensile strength
- All seasons formulation, -10°C to +40°C
- For bonding and filling purposes
- Provides added thermal insulation

#### PRODUCT DESCRIPTION

**Bostik P925 FOAM'N'FIX TURBO MULTI-USE** is a money and time saving multipurpose fast curing and fast setting foam adhesive for bonding stony and concrete type of products as well dry wall panels and decorative elements. **Bostik P925 FOAM'N'FIX TURBO MULTI-USE** can also be used as standard PU foam for insulating and filling gaps and joints around door and window frames as well as in walls.

#### APPLICATIONS

**Bostik P925 FOAM'N'FIX TURBO MULTI-USE** is a multipurpose construction adhesive providing an excellent adhesion to a wide range of substrates, such as dry walls but also stony and concrete type of surfaces and decorative elements. **Bostik P925 FOAM'N'FIX TURBO MULTI-USE** can also be used for insulating and gap filling purposes in joints around door and window frames and in walls.

#### DIRECTIONS OF USE

Canister temperature: +5°C to +30°C (recommended +15°C to +25°C) Application temperature (applies to environment and substrates): -10°C to +40°C (recommended +15°C to +25°C). Hold the canister with the valve turned upwards and affix an applicator gun with NBS-thread onto the canister. We recommend a NBS Gold gun (see instructions in the gun box). Shake the canister vigorously prior to use at least 20 times. Turn canister upside down and apply the foam. To regulate the flow of the foam, loosen the valve at the back of the handle. Protect eyes, wear gloves and protective gear. Apply the adhesive on

the substrate, 5 cm away from the edge and inside the contour, in successive strings with 30 cm distance in between. The recommended diameter of the strings applied with a gun is 10–12 mm; attach the second substrate within its 'open time' of 120 seconds, before the foam adhesive starts to cure. Support is needed until the foam adhesive has cured fully (50–70 minutes). When using the foam adhesive for filling and/or insulating, half fill the cavity and, in case of low humidity, lightly spray the foam with water. The foam will expand to fill the rest. For a complete overview see our website or contact your local sales representative. spray the foam with water. The foam will expand to fill the rest. For fixing window and door frames Bostik recommends to use the **P745 FOAM'N'FIX B2**, **P550 FOAM'N'FIX TURBO B2** or **P345 FOAM'N'FIX 2C B2**. Protect eyes, wear gloves and protective gear. Floor-covering and furniture to be covered with paper or plastic foil. Joints wider and deeper than 4cm should be filled in multiple layers. Wait 15–30 minutes between applications. Before each application lightly spray with water. Only use in well ventilated areas. Store canister upright. Pressurized container! Protect from sunlight and do not expose to temperatures exceeding + 50°C. Do not pierce or burn, even after use. Contains flammable propellants. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition. No smoking. For a complete overview see our website or contact your local sales representative.



## TECHNICAL DATA

Application temperature		-10°C to +40°C
Base		Polyurethane
Curing time		50-70 minutes
Density		15-20 kg/m <sup>3</sup>
Dimensional stability	EN 17333-2	-5% < DS < 0%
Fire behaviour	DIN 4102	B3
Tack free time	EN 17333-3	90-150 seconds
Temperature resistance		-40°C to +90°C
Thermal conductivity		30-35 mW/m.K
Tensile strength		90-95 kPa
Shear strength		45-50 kPa
Yield		30-40 litre

*These values are typical properties and may vary +/-3%*

## LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for permanent water load
- Not suitable for use filling cavities with insufficient moisture

## SURFACE PREPARATIONS AND FINISHING

Substrates must be clean and free of dust, oil and grease. It is important to moisten substrates slightly before use as this improves adhesion and finished cell structure of the foam.

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce

## Bostik Benelux BV

Denariusstraat 11 • NL-4903 RC Oosterhout  
Tel.: +31 (0)162 491 000  
www.bostik.com

## PAINTABILITY

**Bostik P925 FOAM'N'FIX TURBO MULTI-USE** can be painted or covered with sealant/plaster when fully cured.

## CLEANING

Fresh foam can be removed immediately with **Bostik P100 FOAM'N'CLEAN POWER**. After curing surplus foam can be removed with a knife or spatula and the foam surface can be finished.

## COLOUR(S)

- Yellow

## PACKAGING

- 750 ml cans, 12 per box

*For product specifications, please refer to the Online Product Detail Page*

## SHELF LIFE

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 12 months from production date, stored in a dry place.

## CERTIFICATIONS

- EC1 Plus
- A+ French VOC Regulation

## HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via the websites.

## BOSTIK SMART SUPPORT

Smart help digital  
[denbraven.com/](https://denbraven.com/)

Smart help  
+31 (0)162 491 000

