



CRACKFILL

Polymer Modified Cementitious Crack Sealer

TECHNICAL DATA SHEET

DESCRIPTION

Bostik CrackFill is a high performance polymer modified cementitious crack sealer for sealing and repairing in internal and external cracks in plasters and masonry surface

FEATURES & BENEFITS

Single component
Non Shrinking
Better adhesion
Smooth finish

PROPERTIES

Appearance : White Powder
Workability : 20 minutes

APPLICATION PROCEDURE

Develop the crack in a "V" shaped groove
Clean the groove by sprinkle of water to remove all the loose particles and dust
Mix proportion for CrackFill and water in the ratio of 3:1 by volume
Mix CrackFill and water in a clean container
Mix for 2-3 minutes to get smooth homogeneous paste
Apply this paste into the groove with suitable trowel
Finish the surface as required

COVERAGE

35 running meter /kg/for 6X6 mm "V" shaped groove

PACKAGING

CrackFill is supplied in 1,5, kg

STORAGE & SHELF LIFE

CrackFill as supplied shall be stored in a cool and dry place away from sunlight, moisture and high humidity and have a shelf life of 12 months in the original packing.

HEALTH & SAFETY

Crackfill is blend of cement and special additives. Prolonged contact with skin should be avoided. Any splashes should be washed well with water. The use of rubber gloves and safety glasses is recommended. Any splashes on eyes should be flushed immediately with plenty of clean water and medical treatment sought.

WARRANTY

Whilst Bostik India (P) Ltd., strives to ensure that any advice, information or recommendation given are appropriate and correct, it cannot accept any liability directly or indirectly arising out of the products, since the method and place of application of the products are beyond its control. Its guarantee is therefore limited to the quality of materials delivered.

BOSTIK SMART SUPPORT

Smart help digital
bostik.com/

Smart help
+91 80 68297700



