



ULTRA LEVEL PRIMER CONCENTRATE

High Performance Polymer Modified Primer For Porus Substrate

TECHNICAL DATA SHEET

DESCRIPTION

Bostik Ultralevel Primer Concentrate is a high performance one component, specially formulated polymer modified primer designed for porous concrete substrates

RECOMMENDED USES

Bostik Ultralevel Primer Concentrate for use with Bostik range of cementitious self levelling compounds.

FEATURES & BENEFITS

High performance polymer.
Fast drying and rapid tack allows for early application of levelling compound.
For porous concrete/cement surfaces,
Will not re-emulsify in water when dry.
Economical, high coverage rate.
High bond strength.

APPLICATION

PROCEDURE

MIXING

Ultralevel Primer is supplied in a concentrate and required mixing and dilution with water at a rate of 2.1 (2 parts water to 1 part Ultralevel Primer)
DO NOT DILUTE WITH EXCESS WATER.
Prime clean dust free concrete substrate with Ultralevel Primer using a brush, broom or roller. Allow primer to reach a tacky consistency before applying Ultralevel levelling compound. Primer will dry in approximately 40-60 minutes depending on substrate and air temperature.
Ensure no ponding or puddles of the primer is evident prior to the application of the Ultralevel range.
Extremely porous substrates such as weather damaged slabs, aerated lightweight concrete ect. May require a second coat of primer to avoid pinholes and bubbles in the levelling compound.

If a second coat is required allow the first coat to dry prior to application of consecutive coat.

PACKAGING

Ultralevel Primer Concentrate is supplied in a 1 & 5 Litre containers.

COVERAGE

1 litre of Ultralevel Primer diluted with 2 litres of water will cover approximately 8-10m² per litre per coat. Depending upon the porosity of the substrate.

HEALTH AND SAFETY

Suitable protective clothing, dust masks, gloves and eye protection should be worn. If skin irritation occurs, remove contaminated clothing and flush skin thoroughly with water for a minimum of 15 minutes.
For more detailed information refer to Material Safety Data Sheet.

CLEAN-UP

Clean brushes, rollers and equipment with water immediately after use.

STORAGE:

Ultralevel Primer Concentrate has a shelf life of approximately 12 months.

FIRE:

Ultralevel Primer Concentrate is non flammable.

WARRANTY

Whilst Bostik India (P) Ltd., strives to ensure that any advice, information or recommendation given are appropriate and correct, it cannot accept any liability directly or indirectly arising out of the products, since the method and place of application of the products are beyond its control. Its guarantee is therefore limited to the quality of materials delivered.