



Cementone Pave Seal

FAST DRYING CONCRETE AND BRICK PAVING PROTECTOR

Date: 08 July 2015

Fact Sheet No.: TDS00068

YOUR SMART ADVANTAGES

- Clear drying, deep penetration protection
- Resists water, oil and grease
- Enhances the colour of paving

USES

Bostik Pave Seal (formerly known as Cementone Pave Seal) is a clear, low viscosity, solvent based acrylic solution that penetrates deeply into dry concrete, brick, porous tiles etc. Bostik Pave Seal provides excellent resistance to water and dirt. It also enhances the colour of the treated surface.

Bostik Pave Seal is suitable for use to protect drives, paths, patios and other porous exterior paved surfaces.

PRODUCT CHARACTERISTICS

Colour	Transparent
Form	Clear thin liquid
Specific Gravity	0.9 approx.
Composition	Solvent based acrylic resin solution
Product Code	30812235 5 Litre x 4 30812535 25 Litres
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 24 months from date of manufacture in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight and away from heat and sources of ignition. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +30°C
Coverage	Approximately 5 – 8m ² per litre per coat depending on porosity of surface
Drying Times	Foot traffic: Approximately 4 hours Vehicular traffic: Approximately 24 hours
Solvent for Cleaning Up	White spirit

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Pave Seal refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Protective gloves and eye/face protection should be worn
2. Ensure the surface is clean, dry and free from oil, grease, loose materials and moss.
3. Ensure the concrete, brick or tiles are porous and dry internally.
4. Remove any efflorescence from concrete surfaces using Bostik Mortar & Brick Cleaner, as directed. Rinse thoroughly and allow to through dry, not just at the surface.
5. Do not use Bostik Pave Seal on new concrete, allow at least 28 days after laying.
6. Do not apply Bostik Pave Seal onto non-porous materials e.g. quarry tiles, some dense bricks etc.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

7. Do not use Bostik Pave Seal around swimming pools.
8. Always test on a small inconspicuous area and allow to dry prior to full application to safeguard against unwanted changes of appearance to surfaces.
9. Protect adjacent surfaces, ponds and plants from splashing.
10. Shake well before use.

APPLICATION

11. Bostik Pave Seal must only be applied to dry exterior surfaces above ground. Do not apply in wet or frosty conditions.
12. Apply evenly using a soft brush, roller or spray.
13. Work into surface. Do not allow to pool on surface.
14. After 2 – 3 hours apply second coat.
15. A third coat may be required on very porous surfaces.
16. Protect freshly applied product from rain and frost until dry.
17. Leave surfaces to dry completely before use, approx. 4 hours for foot traffic, approx. 24 hours for vehicular traffic.

CLEANING

18. Clean tools and equipment immediately after use with white spirit.
19. Dried product is difficult to remove.

PRECAUTIONS IN USE

Do not apply Bostik Pave Seal in wet or frosty conditions, or if rain is expected. Do not use on new concrete – allow at least 28 days after laying. Do not apply to non-porous materials e.g. quarry tiles, wet moulded concrete slabs and some dense bricks etc. Do not use around swimming pools. Bostik Pave Seal should not be used internally or in enclosed areas where the lingering odour of solvent may be a problem. Efflorescence may still occur after application of Bostik Pave Seal, if the blocks are laid direct onto the ground.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Pave Seal, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.