



Fix it fast...



BOSTIKROLL 25/50/85

- Quick installation which resists plasticiser migration
- High resistance to temperature (-40°C to +120°C)
- Very low VOC emissions: EN 13999 BREEAM / EMICODE EC1 Plus



**ULTRA
RESISTANT
EXTRA-STRONG
BOND**

YOUR SMART ADVANTAGES

- Extra-strong bond
- High temperature resistance (-40°C up to +120°C)
- Quick installation which resists plasticiser migration
- Very low VOC emissions: EN 13999 BREEAM / EMICODE EC1 Plus

USES

Bostik Roll is a double sided reinforced tape. It is quick, easy and clean to install with the added benefit of being odourless, non-flammable and can accept foot traffic immediately. Suitable for all types of skirtings, softfloor coverings covered to form skirting (PVC, rubber), profiles and covings, linoleum skirting, textile skirting (carpet, needle-punched fabric), PVC skirting cable ducting, wooden skirting, protective wall panels (for hospitals, health centers, schools, offices), accessories, (floor or wall-mounted). Multi-subfloors. Efficient alternative to solvent neopren adhesives.

ON SUBFLOORS AS

- Concrete slabs
- Cement screeds
- Calcium sulphate screeds
- Self-leveling compounds
- Plywood, OSB₃
- Metal or non porous substrates

Wall substrates such as plasterboard, gypsum blocks, existing wall coverings. Porous surfaces should be primed with Bostik Universal Primer.

PREPARATION

Ensure the subfloor or wall is clean, sound, dry; of adequate tensile and compression strength, free from laitance, cracks and structural defects. Any contaminants that may hinder adhesion, such as grease, dust, some curing compounds and moisture sensitive adhesive residues must be completely removed.

APPLICATION

Unroll and apply the tape along the subfloor or wall. Press on the entire surface of the protective paper, eliminating any air bubbles. Pull away the protective paper and rub down the flooring or accessories.

PRODUCT CHARACTERISTICS

Composition	Pre-coating based on synthetic resins and reinforced weft
Colour	Translucent
Drying Time	Immediate use
Working time	unlimited
Application Temperature	+10°C to +30°C & HR<70%
Temperature Resistance	-40°C to +120°C
Consumption	1 reel = 50 meters long

PRODUCT CODE	PACKAGING	BOX QUANTITY
30607844	25mm x 50m	8
30607845	50mm x 50m	5
30607846	85mm x 50m	3

FURTHER INFORMATION

For any application not covered please Contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions or use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Roll, available at www.bostik.co.uk

Bostik Ltd.,
Common Road,
Stafford, ST16 3EH, UK.
Tel: +44 (0) 1785 272625
www.bostik.co.uk

Email: laybond.flooring@bostik.com

Bostik Industries Ltd.,
Newtown, Swords,
Co. Dublin, Ireland.
Tel: +353 1 8624900
www.bostik.ie

BOSTIK HOTLINE

Smart help +44 (0)1785 272625

