



# BLU-TACK® COLOUR

THE ORIGINAL RE-USABLE ADHESIVE

16 February 2017

## YOUR SMART ADVANTAGES

- Permanently plastic and pliable
- Reusable
- Australian made
- Non-toxic, suitable for the family
- Tested in accordance to AS/NZS ISO 8124:2012 (Safety of Toys – Part 3)

## USES

Bostik Blu-Tack® Colour is a permanently plastic, reusable multipurpose adhesive. Blu-Tack® is supplied in the form of rectangular strips between sheets of release paper and packed in individual envelopes. Bostik Blu-Tack® is clean and economical in use.

Blu-Tack® Colour has a myriad of uses around the home, office, school, factory or workshop.

Create 3D models or fantastic murals on your window or wall. Holds up posters, cards, children's paintings, party decorations, maps, messages, etc. Telephones and calculators to desks, ornaments to shelves, photos in albums, screws to screwdrivers, model parts during painting, etc.

Holds safety pins, keys, screws, etc. flowers and candles in place for table and flower arrangements.

Cleans fluff from fabric and dirt from typewriters, model railway tracks, etc. May be rolled and manipulated to make 3 dimensional artistic 'models'.

For use on non-porous surfaces: - vinyl coated wallpapers, painted surfaces, glass, and metal.

## PRODUCT CHARACTERISTICS

Colours	Green, pink, blue, orange & yellow
Form	Putty Strips
Composition	Synthetic Polymer Base
Specific Gravity	1.09 approx.
Pack Quantity	10 units

## TYPICAL PERFORMANCE DATA (approx.)

Solubility Insoluble

## DIRECTIONS FOR USE

Read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting [www.bostik.com.au](http://www.bostik.com.au) or by scanning the relevant QR code on pack.

## SURFACE PREPARATION

1. Wash hands before use.
2. Ensure surfaces are clean; dry free from grease and loose materials.

## APPLICATION

Blu-Tack® Colour works because its pressure sensitive.

1. For non-laminated surfaces make a blob by tearing off a piece, pull and stretch into a ball and apply to one surface.
2. For laminated surfaces cut off 3-5cm pieces of Blu-Tack, remove the release paper on one side, apply to one surface, then remove the other release paper.
3. Using good thumb pressure, apply to the other surface.

## REMOVAL

To remove Blu-Tack® Colour, hold and twist off or roll it carefully off the surface. Any remaining shreds can be removed by rolling or dabbing a blob of Blu-Tack over the surfaces.

## STORAGE AND SHELF LIFE

Store away from heat, strong oxidizing agents and acids. Store between 5°C to 30°C. Shelf life is 5 years from the date of manufacture when stored as directed.

# BOSTIK BLU-TACK® COLOUR

## HEALTH & SAFETY

Always read the Technical Data Sheet and Safety Data Sheet (SDS) before handling or use. Full product safety information required for safe use is not included in this data sheet. SDS available by request or at [www.bostik.com.au](http://www.bostik.com.au)

## PRECAUTION IN USE

Do not use Blu-Tack® Colour on absorbent, silk screen printed or hand stencilled wallpaper nor on porous brickwork.

Care should be taken on painted plaster as Blu-Tack® Colour's adhesive qualities may cause paint to come away from wall.

The adhesive properties of Blu-Tack Colour increase over time, so take extra care when removing after a period of months. On some surfaces Blu-Tack Colour can leave an oily mark but this can often be removed using De-Solv-It Sticky Spots, Stain Remover or lighter fluid. Before using these products, we recommend you test on a small inconspicuous area.

Not suitable to support heavy objects. 0.5g holds 105g of load.

FIRE

Non-flammable.

Recommendations and suggestions are for guidance only, since conditions of use are completely out of our control.

**For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.**

## Product codes:

30604201	Blu Tack Colour 75g AU
30615424	Blu Tack Colour 75g China

BOSTIK HOTLINE

Smart help 1800 898 551



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit [www.bostik.com/au](http://www.bostik.com/au)