

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020Revision Date: 20-Oct-2020  
Revision Number 1**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier**

Product Name WOOD ADHESIVE 750 WINTER  
Pure substance/mixture Mixture

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Recommended use Adhesive.  
Uses advised against None known.

**1.3. Details of the supplier of the safety data sheet****Company Name**

Bostik AB  
Strandbadsvaegen 22  
PO Box 903  
25109 Helsingborg, Sweden  
Tel: +46 42 19 50 00  
Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

**1.4. Emergency telephone number**

Emergency Telephone

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 2 - (H319)
Flammable liquids	Category 3 - (H226)

**2.2. Label Elements**

Signal word  
WARNING

**Hazard statements**

H319 - Causes serious eye irritation.  
H226 - Flammable liquid and vapour.

**EU Specific Hazard Statements**

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

[C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction.

## Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 - Wear eye protection/ face protection.  
P264 - Wash face, hands and any exposed skin thoroughly after handling.  
P370 + P378 - In case of fire: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam to extinguish.  
P403 + P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents/ container to an approved waste disposal plant.

## 2.3. Other Hazards

No information available

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Ethanol	200-578-6	64-17-5	10 - <20	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)		01-2119457610-43-XXXX
Isopropyl alcohol	200-661-7	67-63-0	1 - <5	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119457558-25-XXXX
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9	2634-33-5	0.01 - <0.05	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411) (M Factor Acute =1)	Skin Sens. 1 :: C>=0.05%	01-2120761540-60-XXXX
reaction mass of	611-341-5	55965-84-9	<0.0015	Acute Tox. 3	Eye Dam. 1 ::	01-2120764691-

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
 Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
 Revision Number 1

5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]				(H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute = 100 M Factor Chronic = 100	C>=0.6% Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	48-XXXX
---	--	--	--	---	---	---------

**Full text of H- and EUH-phrases: see section 16**

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** May cause redness and tearing of the eyes. Burning sensation.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Treat symptomatically.

## SECTION 5: Firefighting measures

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

## 5.1. Extinguishing media

**Suitable extinguishing media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media** Full water jet. Do not scatter spilled material with high pressure water streams.

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon dioxide (CO<sub>2</sub>).

## 5.3. Advice for firefighters

**Special protective equipment for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. See section 8 for more information. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Eliminate all ignition sources if safe to do so.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

- Advice on safe handling** Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use according to package label instructions. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.
- General hygiene considerations** Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

## 7.2. Conditions for safe storage, including any incompatibilities

- Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep containers tightly closed in a dry, cool and well-ventilated place.

## 7.3. Specific end use(s)

**Specific Use(s)**  
Adhesive.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

**Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.**

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Ethanol (64-17-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	950 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	343 mg/kg bw/d	

Isopropyl alcohol (67-63-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	500 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	888 mg/kg bw/d	

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
 Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
 Revision Number 1

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

<b>Derived No Effect Level (DNEL)</b>			
<b>Ethanol (64-17-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	114 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	206 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	87 mg/kg bw/d	

<b>Isopropyl alcohol (67-63-0)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	89 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	319 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Ethanol (64-17-5)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	154 mg/l
Marine water	15.4 mg/l
Sewage treatment plant	100 mg/l

<b>Isopropyl alcohol (67-63-0)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	140.9 mg/l

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

Marine water	140.9 mg/l
Sewage treatment plant	2251 mg/l
Freshwater sediment	552 mg/kg dry weight
Marine sediment	552 mg/kg dry weight
Soil	28 mg/kg dry weight

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

**Eye/face protection** Tight sealing safety goggles.  
**Hand protection** Wear protective gloves. Gloves must conform to standard EN 374. Recommended Use: Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves should be replaced regularly and if there is any sign of damage to the glove material.  
**Skin and body protection** Suitable protective clothing.  
**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment. Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** Liquid  
**Appearance** Viscous Liquid  
**Colour** White  
**Odour** Alcohol  
**Odour threshold** No information available

Property	Values	Remarks • Method
<b>pH</b>	No data available	
<b>pH (as aqueous solution)</b>	6 - 7	
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	90 °C	
<b>Flash point</b>	32.5 °C	CC (closed cup)
<b>Evaporation rate</b>	No data available	
<b>Flammability (solid, gas)</b>	Not applicable for liquids .	
<b>Flammability Limit in Air</b>		
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Vapour pressure</b>	No data available	
<b>Vapour density</b>	No data available	
<b>Relative density</b>	No data available	
<b>Water solubility</b>	Miscible in water	
<b>Solubility(ies)</b>	No data available	
<b>Partition coefficient</b>	No data available	
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>	No data available	
<b>Kinematic viscosity</b>	No data available	

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

Dynamic viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available

## 9.2. Other information

Solid content (%)	No information available
VOC Content (%)	No information available
Density	1.05 g/cm <sup>3</sup>

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

#### Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

### 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### Product Information

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).

Skin contact Specific test data for the substance or mixture is not available. Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available.

#### Symptoms related to the physical, chemical and toxicological characteristics



# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

**Symptoms** May cause redness and tearing of the eyes.

## Numerical measures of toxicity

### Acute toxicity

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethanol 64-17-5	6200 - 15000 mg/kg (Rattus) OECD 401		=124.7 mg/L (Rattus) 4 h
Isopropyl alcohol 67-63-0	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus cuniculus)	=72600 mg/m <sup>3</sup> (Rattus) 4 h
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	
reaction mass of 5-chloro-2-methyl-2H-isothiazol- 3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	=53 mg/kg (Rattus)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

#### Ecotoxicity

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Ethanol 64-17-5	EC50 72hr 12.9 g/l (Selenastrum capricornutum) NOEC 3.24 g/l (Skeletonema costatum)	LC50: >100mg/L (96h, Pimephales promelas)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	LC50: (48h, Daphnia magna) EC50: =12.34 mg/L		
Isopropyl alcohol 67-63-0	EC50 72 h > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h > 1400000 ?g/L (Lepomis macrochirus )	-	EC50: =13299mg/L (48h, Daphnia magna)		
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Ethanol 64-17-5	-0.32	-
Isopropyl alcohol 67-63-0	0.05	-
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.7	6.95
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	-	3.16

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

### PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Ethanol 64-17-5	The substance is not PBT / vPvB PBT assessment does not apply
Isopropyl alcohol	The substance is not PBT / vPvB

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

67-63-0	PBT assessment does not apply
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	The substance is not PBT / vPvB

## 12.6. Other adverse effects

Other adverse effects No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition).

### Land transport (ADR/RID)

14.1 UN number	UN1133
14.2 Proper Shipping Name	Adhesives Ethanol
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III, (D/E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None
Classification code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	30

### IMDG

14.1 UN number	UN1133
14.2 Proper Shipping Name	Adhesives Ethanol
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III, (32.5°C c.c.)
14.5 Marine pollutant	Np
14.6 Special Provisions	223, 955
Limited Quantity (LQ)	5 L
EmS-No	F-E, S-D
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A3
Limited Quantity (LQ)	10 L
ERG Code	3L

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Biocidal Products Regulation (EU) No 528/2012 (BPR)**

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

##### **Dangerous substance category per Seveso Directive (2012/18/EU)**

P5a - FLAMMABLE LIQUIDS  
P5b - FLAMMABLE LIQUIDS  
P5c - FLAMMABLE LIQUIDS

##### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

##### National regulations

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

## France

### Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Ethanol 64-17-5	RG 84
Isopropyl alcohol 67-63-0	RG 84
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	RG 65

## Germany

### Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R10), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 3

Water hazard class (WGK) slightly hazardous to water (WGK 1)

## Netherlands

### List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands
Ethanol 64-17-5	Present Fertility (Category 1A); Development (Category 1A); Can be harmful via breastfeeding

## Sweden

Occupational exposure limits AFS 2018:1

## Denmark

Registration number(s) (P-no.) 426061

MAL-Code 1-1 (1993)

## Norway

Registration number(s) (PRN-no.) 55296

## 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour  
H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H310 - Fatal in contact with skin  
H314 - Causes severe skin burns and eye damage  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H330 - Fatal if inhaled  
H336 - May cause drowsiness or dizziness  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H411 - Toxic to aquatic life with long lasting effects

# SAFETY DATA SHEET

WOOD ADHESIVE 750 WINTER  
Supersedes Date: 20-Oct-2020

Revision Date: 20-Oct-2020  
Revision Number 1

---

## Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision Date:** 20-Oct-2020

## Indication of changes

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**