

FIX A570 MULTI TACK

TACKIFIER ADHESIVE SUITABLE FOR MANY TYPES OF TILES

BENEFITS/CHARACTERISTICS

- ✓ Produces a tape effect
- ✓ Rollable adhesive
- ✓ Enables replacement and recycling of floor coverings
- ✓ Good environmental choice, M1 and EC1 Plus



AREA OF APPLICATION

PRODUCT DESCRIPTION

FIX A570 is a water-based tackifier adhesive. Enables replacement and recycling of floor coverings. Environmentally friendly with low emission values, compliant with emission class EC1 Plus and M1.

USES

For installation of textile floor tiles on absorbent and dense surfaces indoors. Suitable for areas with underfloor heating and wheelchair use. An excellent choice for office premises.

Recommended materials:

- ✓ Textile floor tiles
- ✓ PVC floor tiles
- ✓ Patterned textile flooring with felt backing

PRODUCT INFORMATION

ART. NO.	PACK SIZE	VOLUME	EAN
30620217	10 L	10 KG	7311020081102

PRODUCT CHARACTERISTICS

Colour	White
Density	1.0 kg/litre
Binder	Polymer dispersion of acrylate type
Adhesion time*	Normally absorbent surface: 45–60 min Dense surface: 1.5–4 hours
Open time*	Permanent tacky film (in dust-free conditions)
Walkable	Can be walked on immediately. Full strength is achieved after 24 hours.
Curing time	30–120 minutes
Coverage	6–12 m ² /L
Working conditions	Temperature at least +15°C. The best results are achieved at around 20°C with around 60% RH.

* These values are measured at +23°C with 50% relative humidity on a normally absorbent surface. These values may deviate from the above depending on the surface and temperature.



APPLICATION INSTRUCTIONS

PREPARING THE SURFACE

Always follow the flooring manufacturer's directions. The information below is only intended as supplementary information regarding the actual adhesion process. The surface must be clean, flat, strong and free of dust, dirt, glue residue and old paint. If you need to level out the surface, we recommend that you use a Bostik Floor Screed intended for the purpose. For adhesion to concrete surfaces, the moisture content must not exceed the maximum values specified in AMA Hus. The adhesive, floor covering and substrate should have a temperature of at least +15°C. The relative humidity (RH) in the substrate must not exceed 85% for concrete and 8-12% for chipboard. For non-absorbent surfaces such as high-performance concrete, we recommend application of at least a 10 mm thick layer of Bostik Floor Screed. For particularly absorbent surfaces we recommend the use of Bostik Primer 6000.

APPLICATION METHOD

Absorbent surfaces: Apply the adhesive with a roller (approx. 12 mm) and allow it to dry for approx. 45-60 minutes. Install the flooring material as soon as possible to reduce the risk of dust gathering on the adhesive film. If the adhesive is to be used for permanent adhesion, allow it to dry for 5-10 minutes before installing the flooring material.

Dense surfaces: Apply the adhesive with a roller and allow to dry for approx. 1.5-4 hours until the adhesive no longer feels wet to the touch. Lay the flooring material on the adhesive. Press/rub out all of the air under the flooring material (be particularly thorough around the edges).

For best results, a floor roller should be used. NOTE - Always follow the flooring manufacturer's directions.

REPLACEMENT OF FLOORING MATERIAL

Carefully lift up the floor tiles/flooring material by starting in one corner and working towards the middle. Glue residue can be removed with white spirit.

COVERAGE

6-12 m²/L depending on the surface and choice of application method. Apply with a roller.

STORAGE/SHELF LIFE

12 months in a dry, cool location in unopened packaging at a storage temperature from +10°C to +20°C. The product should be stored frost-free.

CLEANING

With water before the adhesive has dried. Dried adhesive can be removed mechanically or with white spirit.

SAFETY

A safety data sheet is available on request. Always have the packaging or label at hand if you need to seek medical care. Keep the product out of the reach of children. If the adhesive comes into contact with your eyes, immediately rinse your eyes with water. If the adhesive comes into contact with your skin, wash your skin with soap and water. www.bostik.se

LIABILITY

Disclaimer: The technical data we report, as well as our instructions and recommendations, are all based on a variety of tests and on our experience. They are intended to help the user achieve the best possible results. As the conditions at the user's premises are beyond our control, we cannot accept any liability for the results achieved when using the product.

BOSTIK SERVICE

info.se@bostik.com
www.bostik.se

