

# H760

## SEAL'N'FLEX PRO SEAL PREMIUM QUALITY ELASTIC PROFESSIONAL JOINT SEALANT

### TECHNICAL DATA SHEET

#### BENEFITS

- Free of isocyanates, solvents, phthalate and silicones
- Durable, permanent soft elastic
- 100% bubble free curing
- High elongation at break and movement capacity
- Good resistance to UV, weather and water
- Paintable
- Adheres perfectly without primer on most, even damp, surfaces

#### PRODUCT DESCRIPTION

**Bostik H760 SEAL'N'FLEX PRO SEAL** is a premium isocyanate, phthalate and solvent free quality high modulus sealant for construction and dilatation joints. **Bostik H760 SEAL'N'FLEX PRO SEAL** fulfil BREEAM specifications mentioned in chapter 'Health and Wellbeing', Hea 02 Indoor Air Quality, regarding volatile organic compound (VOC) emission levels (products).

#### APPLICATIONS

**Bostik H760 SEAL'N'FLEX PRO SEAL** is specifically developed as a universal sealant for sealing construction and expansion joints and joints in pedestrian walkways where extreme low emissions are required.

#### DIRECTIONS OF USE

A joint with the correct dimensions is able to absorb movements between building materials. The joint depth should always be in the correct relationship of the joint width. A general rule is the ratio of joint depth to the width of the joint with a joint width up to 10mm is 1:1, with a minimum of 5mm in width and depth. For joints wider than 10mm, the depth is the width divided by 3 plus 6mm.



#### TECHNICAL DATA

100% modulus	ISO 8339	0,70 N/mm <sup>2</sup>
Application rate		100-200 g/min
Application temperature		+5°C to +40°C
Base		Hybrid
Curing time	@ +23°C/50% RH	2 mm/24 hours
Density	ISO 1183-1	1,45 g/ml
Elongation at break	ISO 8339	450%
Flow	ISO 7390	< 2 mm
Frost resistance during transportation		Up to -15°C
Joint movement		25%
Shore A hardness	DIN 53505	28
Skin formation	DBTM 10.00	30 min. @ +23°C/50% RH
Temperature resistance		-30°C to +70°C
Tensile strength	DIN 53504	1,20 N/mm <sup>2</sup>

*These values are typical properties and may vary +/-3%*

#### LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for natural stone and mirrors
- Not suitable for natural stone and chlorides (pools)
- Not suitable for continuous water load

## SURFACE PREPARATIONS AND FINISHING

Application temperature + 5°C to + 40°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Clean substrates with **Bostik T100 UNIVERSAL CLEANER**. **Bostik H760 SEAL'N'FLEX PRO SEAL** adheres perfectly without the use of a primer to most non porous substrates. Porous substrates to be pre-treated with **Bostik T300 UNIVERSAL PRIMER**. Always test adhesion prior to application. Use **Bostik T500 FINISHING SOAP** to smooth the joint.

## PAINTABILITY

**Bostik H760 SEAL'N'FLEX PRO SEAL** is paintable with water based and most 2 component paints. Synthetic paints can dry slower. We recommend testing compatibility with paint prior to application. If **Bostik H760 SEAL'N'FLEX PRO SEAL** is being painted over (not necessary), we recommend slightly sanding the sealant and the junction surfaces prior to use with Scotch-Brite. For the best results, we recommend painting within a few days of application.

## CLEANING

Uncured material and tools can be cleaned by using **Bostik T100 UNIVERSAL CLEANER**. Cured material can only be mechanically removed. Hands can be cleaned with **Bostik T150 CLEANING WIPES**.

## COLOUR(S)

- White
- Ivory
- Concrete Grey
- Mid Grey
- Anthracite
- Black

## PACKAGING

- 290 ml Cartridge, 12 per box

*For product specifications, please refer to the Online Product Detail Page*

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce

## Bostik

De Voerman 8 • NL-5215 MH 's-Hertogenbosch  
Tel.: +31 (0) 73 6244 244  
www.bostik.com

## SHELF LIFE

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 18 months from production date, stored in a dry place.

## HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via the websites.

## CERTIFICATIONS

- Bostik Flex-IQ®
- F-EXT-INT-CC 25HM
- PW-EXT-INT-CC 25HM
- Emicode EC1 Plus
- Emission Certificate M1
- A+ French VOC Regulation

## BREEAM

BREEAM is the world's leading sustainability assessment method for master planning projects, infrastructure and buildings. It recognises and reflects the value in higher performing assets across the built environment lifecycle, from new construction to in-use and refurbishment.

Bostik is able to support the BREEAM international scheme to provide independent third party certificates, as we can do for this product the **Bostik H760 SEAL'N'FLEX PRO SEAL**. Due to the EC1 Plus, Bostik can provide the required 'proof' accordingly the Hea 02 Indoor Air Quality, regarding volatile organic compound (VOC) emission levels.

## BOSTIK SMART SUPPORT

Smart help digital  
[Bostik.com/](https://www.bostik.com/)

Smart help  
+31 (0)162 491 000

