



## Limguide – giltig från 220321

Beläggning	Limtyper	Limningsmetod		Lim-mängd/ limspridare
		Sugande underlag	Svagt sugande underlag	
<b>PVC-mattor homogena och heterogena</b> Palettone Pur, Pearlazzo Pur, Prestige Pur, Classic Mystique Pur, 2000 Pur, XL PU, Expona Flow Pur, Bloc Pur, Forest fx Pur, Silentflor Pur,	STIX A800 PREMIUM STIX A720 POWER STIX A600 EVOLUTION STIX A555 ULTRA STIX A500 COMBI	Våtlimning	Sen våtlimning	4-5 m <sup>2</sup> /ltr – A2
<b>PVC-golv, halkhämmande</b> Polysafe Standard, Polysafe Wood fx Pur, Polysafe Verona Pur, Polysafe Quattro Pur, Polysafe Hydro	STIX A800 PREMIUM STIX A720 POWER STIX A600 EVOLUTION STIX A555 ULTRA STIX A500 COMBI	Våtlimning	Sen våtlimning	4-5 m <sup>2</sup> /ltr – A2
<b>Stegljudsmatta - Acoustifoam</b>	STIX A800 PREMIUM	Våtlimning	Sen våtlimning	4-5 m <sup>2</sup> /ltr – A2
<b>LVT löslagd –</b> Expona Simplay Wood, Expona Simplay Stone	FIX A760 TECH	Häftlimning	Häftlimning	5-8 m <sup>2</sup> /ltr – appliceras med roller
<b>LVT plattor - permanentlimmad</b> Expona commercial Pur, Expona Design, Expona Control, Affinity2 <sup>55</sup> Pur	STIX A800 PREMIUM STIX A720 POWER STIX A555 ULTRA	Våtlimning	Rekommenderas ej	4-5 m <sup>2</sup> /ltr
<b>Väggmattor</b> Polyclad Pro Pu, Polyclad Plus Pu	STIX A800 PREMIUM STIX A720 POWER STIX A555 ULTRA	Våtlimning	Sen våtlimning	4-5 m <sup>2</sup> /ltr – A2

# artigo

<b>Gummi – rullvara och plattor 3mm</b> Artigo Screed ECO, Kayar, ND-Uni, Grain, Lava, Natura	STIX A800 PREMIUM	Våtlimning	Sen våtlimning	4-5 m <sup>2</sup> /ltr – A2
<b>Gummi – rullvara och plattor 2mm</b> Granito, Dharma	STIX A800 PREMIUM STIX A720 POWER STIX A555 ULTRA	Våtlimning	Sen våtlimning	4-5 m <sup>2</sup> /ltr – A2
<b>Akustikgolv – X-Elastic</b> Artigo Screed ECO, Kayar, ND-Uni, Grain, Lava, Natura, Granito, Dharma	STIX A800 PREMIUM STIX A720 POWER STIX A600 EVOLUTION STIX A555 ULTRA STIX A500 COMBI	Våtlimning	Sen våtlimning	4-5 m <sup>2</sup> /ltr – A2
<b>BS Strong/BS Zeus - plattor</b>	STIX A800 PREMIUM  STIX P956 2K – vid tung belastning eller fuktutsatta miljöer	Våtlimning  Våtlimning	Sen våtlimning  Våtlimning	4-5 m <sup>2</sup> /ltr – A2  400-1200 g/m <sup>2</sup> beroende på underlag och val av appliceringsmetod – se TDS
<b>Gummi – plattor 2,7 mm BS Classic</b>	STIX A800 PREMIUM  STIX P956 2K – vid tung belastning eller fuktutsatta miljöer	Våtlimning  Våtlimning	Sen våtlimning  Våtlimning	4-5 m <sup>2</sup> /ltr – A2  400-1200 g/m <sup>2</sup> beroende på underlag och val av appliceringsmetod – se TDS



<b>Textila plattor – Paragon</b> Inspiration collection, Vaopur, Diversity, Diversity Groove, Sirocco. Sirocco Stripe, Macaw, Macaw Stripe, Maestro38, Toccarre, Workshop Loop, Workshop Linear, Strobe	FIX A570 MULTITACK FIX A70 TECH	Häftlimning	Häftlimning	5-10 m <sup>2</sup> /ltr – appliceras med roller
--	------------------------------------	-------------	-------------	--