



Plasterer's Stabilising Primer

PRIMES AND STABILISES PROBLEM SURFACES ON PREVIOUSLY PLASTERED WALLS

Date: 24 August 2020

Fact Sheet No.: TDS01648

YOUR SMART ADVANTAGES

- Excellent key for skim coats
- Coloured for controlled application
- No mixing - easy to apply

USES

Bostik Plasterer's Stabilising Primer with Plasprime® Technology has been specially developed for the plastering professional. It primes and stabilises most interior surfaces, including previously plastered walls, prior to the application of new plaster. Bostik Plasterer's Stabilising Primer is green in colour for easy application and contains 20% recycled material. It can be applied over porous and non-porous areas to give a surface that dries evenly giving excellent adhesion and a faster, easier finish.

It has been specially developed for preparing old walls prior to re-skimming and can be applied over brick, blocks, concrete, plaster, plasterboard and render. It stabilises problem surfaces including: well-adhered emulsion paint, wallpaper adhesive residues, old plaster/render, porous and non-porous surfaces.

PRODUCT CHARACTERISTICS

Colour	Green
Form	Viscous liquid
Specific Gravity	1.2 approx.
Composition	Water based polymers and recycled material
Product Code	30806585 5 litre bucket 30806586 10 litre bucket
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the lid is

secure. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	Above +5°C
Coverage	3 - 4m ² per litre (depending on the porosity and texture of the surface being prepared)
Drying Times	24 hours approx. (depending on ambient conditions)
Cleaning	Clean tools and equipment with water immediately after use. Remove any splashes, as dried product is difficult to remove

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Plasterer's Stabilising Primer, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Surfaces must be dry, clean, and free from grease, dust or loose material. Mechanically remove any loose or flaking material. Any existing paint should be checked for soundness and adhesion. Do not apply directly onto existing wallpaper.
2. Ensure that any surface to be plastered is strong enough to support the weight of the new plaster.
3. Bostik Plasterer's Stabilising Primer will not make up for defective surfaces and the bond will only be as good as the weakest part of the system i.e. when applied to

paint. Bostik are not responsible for failure of an underlying substrate.

IMPORTANT: For internal use only and not suitable for priming prior to adhesive fixing of plasterboards. For glossy surfaces, external use, bonding renders and very high absorbency backgrounds use Bostik Renderer's Stabilising Primer.

4. Tape over any obvious joints or cracks with plasterer's scrim tape.
5. Any chalky or high suction surfaces should be treated with a 1:1 dilution of Bostik SBR, which can be applied by roller. Allow to dry completely before applying Bostik Plasterer's Stabilising Primer.

APPLICATION

6. Bostik Plasterer's Stabilising is primarily designed to allow skim finish plaster to be applied to surfaces that would not normally accept a finish such as emulsion painted walls. For other specific applications, please contact Bostik Technical Services.
7. Apply Bostik Plasterer's Stabilising Primer straight from the bucket with a soft brush to give an even texture over the entire surface.
8. Allow to dry completely. Drying times are dependent on the porosity of the surface and ambient conditions.
9. Once dry, apply new plaster in the usual way.

CLEANING

10. Clean tools and equipment with water immediately after use. Remove any splashes, as dried product is difficult to remove.

PRECAUTIONS IN USE

Not suitable for use with dot and dab applications. Not suitable for exterior use, or on glossy surfaces such as ceramic tiles. For these applications, we recommend using Bostik Renderer's Stabilising Primer.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Plasterer's Stabilising Primer, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com