



# Watertite

## Flexible Tanking System

Date: 21 August 2020

Fact Sheet No.: TDS01971

### YOUR SMART ADVANTAGES

- Ideal for showers and wet rooms
- Highly flexible seal against moisture Penetration
- Includes a flexible self adhesive tape & two rubber collars

### USES

Bostik Watertite is a highly flexible, ready to use Tanking System for fast, effective and secure sealing against moisture penetration under ceramic, porcelain, natural stone tiles or slabs. The system comprises a paste to seal out moisture, a flexible self-adhesive jointing tape to ensure complete waterproofing on internal and external corners and two rubber collars for the sealing of sanitary fittings. It also provides a universal roller for application of the Tanking Paste.

Substrates suitable for sealing include concrete, masonry (flush jointed), plaster (e.g. cement and lime cement plaster, gypsum boards), expanded and light weight concrete, cement screed, mastic asphalt jointless floors and marine ply or weatherproof boards.

### PRODUCT CHARACTERISTICS

Colour	Grey
Form	Paste
Composition	Solvent Free Liquid
Product Code	30610392 9 kg kit
Storage/Shelf Life	Store and transport this container in a secure upright position. Store for up to 24 months from date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range +5°C to +25°C. Protect from frost.

### TYPICAL PERFORMANCE DATA (approx.)

Application Temperature	+5°C to +25°C
Coverage	6m <sup>2</sup> approx. per 8kg Bostik Watertite Flexible Tanking Kit
Drying Times	24 hours at 20°C on standard backgrounds

### DIRECTIONS FOR USE

**IMPORTANT:** Before using Bostik Watertite refer to the relevant Health & Safety Data Sheet, available at [www.bostik.co.uk](http://www.bostik.co.uk).

Tiling and grouting should be carried out in accordance with the relevant British Standards Codes of Practice.

### PREPARATION

1. Ensure that all surfaces are clean, dry, sound and free from dust, grease or any contaminating barrier.
2. Make good any unsound areas and remove flaky or peeling layers before using Bostik Watertite Flexible tanking system.
3. Absorbent substrates should first be primed with Bostik AP250 prior to applying Bostik Watertite Flexible tanking paste.

### APPLICATION

1. Apply the first coat of Bostik Watertite Flexible Tanking System Paste to the walls and floors, paying particular attention to corner joints.
2. Use the roller provided. Now apply the Bostik Watertite Sealing paste
3. Tape to the dried first coat of paste on all areas between walls and floors, and internal and external corners.
4. For pipe penetrations and drains, seal these using the two rubber sealing collars provided.
5. Apply a second coat of Bostik Watertite Flexible Tanking System Paste onto the first coat, again paying

particular attention to pipe penetration, drains and corner joints.

7. Inspect the complete installation to ensure that it is a seamless covering with no apparent cracking.
8. Leave for at least 24 Hours before tiling.
9. After this the background is suitable for Bostik Cementitious Adhesives, follow recommendations for use of adhesives with particular substrates.

**Important:** Not recommended for use externally, in conditions of total immersion (underwater areas) or as a barrier to prevent ingress of water from the background or base (e.g. not for use as a DPM).

### Health and Safety

Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE; A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE(3:1).

May produce an allergic reaction. Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. Wear suitable protective clothing, gloves and eye/face protection.

REFER TO PRODUCT DATA AND SAFETY DATA SHEETS FOR FULL INSTRUCTIONS

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.co.uk](http://www.bostik.co.uk) for advice.


Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

### Contents

- 8kg Bostik Watertite Flexible Tanking Paste
- 5m roll of Flexible Self-adhesive Jointing Tape
- 2 x Rubber Sealing Collars
- 1 x Universal roller

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>