



FOAM & GUN CLEANER™

POWERFUL POLYURETHANE FOAM CLEANER

KEY FEATURES

- Removes uncured polyurethane foam and residue
- Cleans and rinses foam applicator guns
- Fast acting and easy to apply

DESCRIPTION

Bostik Foam & Gun Cleaner™ is a cleaner designed to remove fresh polyurethane residue and foam and to rinse and clean foam guns after use. It will NOT dissolve cured foam.

DIRECTIONS FOR CLEANING UNCURED FOAM

- Remove black cap from top of can.
- Attach spray nozzle head to valve.
- Test surface before proceeding as acetone will dissolve most types of coatings and can affect dyes and finishes.
- Point can and nozzle towards surface that contains uncured foam. Carefully spray uncured foam directly with cleaner

DIRECTIONS FOR CLEANING FOAM APPLICATOR GUN

- Unscrew can of foam from gun.
- Follow cleaning instructions at left to remove any uncured foam from gun coupling and nozzle prior to attaching the cleaner can to gun.
- If spray nozzle is attached to foam cleaner can, remove spray nozzle and attach gun to can, being sure to screw on gun until seal is tight. Do not over tighten.
- Aim gun into container suitable for dispensing of cleaner, such as a can or box.
- Pull trigger several times until cleaner extrudes from nozzle.
- Release trigger and wait 3 minutes for cleaner to soak in gun.
- Pull trigger multiple times, dispensing cleaner into container until clear solvent is dispensed from nozzle of the gun.
- Attach new can of foam sealant to applicator gun or store gun until next use.

STORAGE/SHELF LIFE

Product shelf life is 12 months under normal storage conditions between 40°F (4°C) and 80°F (27°C). Temperatures should never exceed 120°F (49°C) for maximum shelf life and safety. Store in cool, dry, frost-free conditions.



LIMITATIONS

- Wear chemical resistant goggles, nitrile gloves and suitable work clothing during use.
- PREVENT SKIN AND EYE CONTACT.
- EXTREMELY FLAMMABLE. Vapor may migrate to other rooms. Do not use near open flame or smoke during use. Shut off all pilot lights and all sources of ignition including, but not limited to candles, space heaters and halogen lamps.
- Provide adequate ventilation during use.
- Use mechanical ventilation to maintain exposure below TLV. If TLV is exceeded, use appropriate NIOSH approved respirator.
- Use in vertical position only.

PACKAGING

Available in 13.78 oz (408 mL) cans, 12 per case. 96 cases per pallet.

WARNING

CONTENTS AND FUMES MAY BE HARMFUL IF SWALLOWED OR INHALED. CONTENTS AND FUMES MAY CATCH FIRE. CONTAINER MAY EXPLODE IF HEATED. MAY IRRITATE EYES, SKIN AND RESPIRATORY TRACT. Do not smoke. Do not swallow. Do not get in eyes, on skin or on clothing. Do not breathe fumes. Do not puncture. Do not burn. Use only in a well-ventilated area or wear a mask. Excessive inhalation of vapor, intentional misuse by concentrating and inhaling vapor may be harmful or fatal. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Handle with care. Wash thoroughly after handling. Store in a cool, dry, well-ventilated area away from heat, ignition sources and direct sunlight. Do not reuse container.

KEEP OUT OF REACH OF CHILDREN

FIRST AID TREATMENT

tains acetone, isobutane, and propane. If in eyes or on skin, rinse with water for at least 15 minutes. If on clothes, remove clothes. If inhaled, move person to fresh air. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.

SEE SAFETY DATA SHEET

CHEMICAL EMERGENCY: 800-424-9300 (USA),
703-527-3887 (International)

MEDICAL EMERGENCY: 866-767-5089

BOSTIK HOTLINE

Smart help
1-800-726-7845

Bostik, Inc.
11320 W. Watertown Plank Road
Wauwatosa, WI 53226
www.bostik.com/us

