





NEW SMART AND EYE CATCHING



18 kg = 60 m³



Range colour band, helps to quickly identify the field of use



Clear **pictos** to highlight main characteristics

of the products

Simple **drawing** to directly show the use of the product A Constant of the second secon

Bostik

Destination and benefits in **6 languages** on the facing



NEW NAMES LOGICAL AND EASY TO UNDERSTAND

The new names come in three parts. The first corresponds to the market segment, the second part expresses the technology and the quality level and the last the product characteristic...

FOR ALL YOUR NEEDS

With the Bostik flooring range you get multiple systems which answer all of the technical requirements an installer may face on a jobsite.







RENO / Subfloor reparation HYTEC / Damp proof membranes GRIP / Primers TECHNIS / Screeds SL

/ Self-leveling compounds







WOOD FLOOR

Adhesives for all kinds of solid and engineered wood floors

SOLUTIONS AVAILABLE FOR ALL INDUSTRIES













10 во





46 BC







Dispersion adhesives for LVT design coverings, homogeneous and heterogeneous PVC coverings (sheets and tiles), cushioned vinyl coverings, rubber coverings up to 4 mm thickness with a smooth, polished back and a smooth usable surface, linoleum coverings and cork coverings with PVC underside and PVC coverings.

ORGANICALLY BASED
 GOOD INITIAL ADHESION
 HIGH SHEAR STRENGTH

PRODUCT CHARACTERISTICS

- Waiting time: 10 minutes

- Laying time: approx. 20 minutes Apply pressure to the floor covering
- again after 40 minutes
- Walk on time: 24 hours
- Coverage: 320-360g/m²



во 47



/ STIX

SOFT FLOOR ADHESIVES



STIX A800 PREMIUM ULTRA-HIGH PERFORMANCE FOR ALL TYPES OF SOFT FLOOR COVERING

High-performance acrylic adhesive for laying soft floor covering: LVT, rubber, and homogeneous and heterogeneous PVC (tiles or strips), linoleum strips, semi-flexible tiles. For residential and commercial projects.

IDEAL FOR LVT AND RUBBERS

SHORT DRYING TIME

HEAVY TRAFFIC

PRODUCT CHARACTERISTICS

- PVC drying time: 10–15 minutes
- Rubber: 5 minutes (application on fresh compound)
- PVC open time: 60 minutes Rubber: 30 minutes

F

12 h

- Foot traffic: 12 hours
- Curing time: 24-48 hours
- Coverage: 250-400g/m²



STIX A550 POWER ELASTIC PREMIUM ADHESIVE ELASTIC COVERING

Dispersion adhesives for LVT designer coverings, PVC coverings (sheets and tiles), cushioned vinyl coverings, rubber coverings up to 4 mm thickness with a smooth, polished back and a smooth usable surface, linoleum coverings and cork coverings with PVC underside and PVC coverings.

© GOOD INITIAL ADHESION

SHORT WAITING TIME

HIGH RETENTION CAPACITY

PRODUCT CHARACTERISTICS

EC I

Wem!

MI

SOLVEN FREE Waiting time: 10 minutes
 Laying time: approx. 20 minutes
 Apply pressure to the floor covering again after 40 minutes
 Walk on time: 24 hours



EC 1



STIX A540 MULTI PLUS SMART MULTI ADHESIVE

Multifunctional dispersion adhesives for PVC coverings (sheet and tiles), LVT design coverings in planks and tiles, cushioned vinyl coverings, linoleum, rubber coverings with smooth surface, carpets with different backing, as well as coconut and sisal coverings.

GOOD INITIAL ADHESION

VERSATILE

ECONOMIC

PRODUCT CHARACTERISTICS

 Waiting time: 5 minutes
 Laying time: 10-15 minutes. Apply pressure to the floor covering again after 45 minutes
 Walk on time: 24 hours
 Coverage: 320-650g/m²

<u>....</u>

kg



STIX A300 MULTI FLOOR HIGH-PERFORMANCE ADHESIVE FOR ALL TYPES OF PVC AND ACOUSTIC COVERING

Multipurpose acrylic adhesive for laying soft floor covering: Homogeneous and heterogeneous PVC, carpet with any type of backing, and natural fibres. Also suitable for shower units with PVC floors and walls. Linoleum and rubber acoustic mats. Wall panels. For residential and commercial projects.

OVER UTINE

STRONG, RAPID CURING

ALL PREMISES

•

EC 1

ow emb

Boeth Gutter BoghtDausen Z-155.13-28 PRODUCT CHARACTERISTICS

- Drying time: 10–15 minutes
- Open time: 50-60 minutes
- Foot traffic: 12 hours
- Curing time: 24–48 hours - Coverage: 250–400g/m²



EC 1





STIX A100 PROJECT RESIDENTIAL FLOORING INCLUDING: PVC, CARPET, NATURAL FIBRES

Acrylic adhesive for laying soft floor covering: Heterogeneous PVC, carpet and natural fibres. Private or low-traffic facilities (residential).

HIGH YIELD

EASY APPLICATION

REDUCED ODOUR

PRODUCT CHARACTERISTICS

Drying time: 10–15 minutes
Open time: 45–50 minutes
Foot traffic: 12 hours

- Curing time: 24–48 hours

- Coverage: 250–400g/m²





TEXTILES CARPETS





STIX A775 TEX ECO+ SUSTAINABLE ADHESIVE FOR CARPETS AND TEXTILE COVERINGS

Very low-emission dispersion adhesive material for textile coverings and needle felt with different backings and strong internal tension. Based on renewable raw materials.

ORGANICALLY BASED

FAST INITIAL ADHESION
 HIGH RETENTION CAPACITY

PRODUCT CHARACTERISTICS

Waiting time: 10-15 minutes
Laying time: 10-15 minutes
Walk on time: 24 hours
Coverage : 400-550g/m²





STIX A530 TEX POWER PREMIUM ADHESIVE FOR TEXTILE COVERINGS

Very low-emission dispersion adhesive material for textile coverings with different backings. Particularly suitable for all types of needle fleece coverings.

HIGH STRENGTH

IIGH SHEAR STRENGTH

SHORT WAITING TIME

PRODUCT CHARACTERISTICS

- Waiting time: 5 minutes
- Laying time: 10-15 minutes. Apply pressure to the floor covering again after 30 minutes
- Walk on time: 24 hours - Coverage: 415–730g/m²



SOFT FLOOR ADHESIVES

0

EC 1 US





STIX A320 TEX PROJECT CARPETS, TEXTILES AND NATURAL FIBRES

Acrylic adhesive for installing carpets with foam, non-woven felt and Actionbac. Needle-punched with or without backing. Coco sisal and seagrass with latex backing.

IIGH INITIAL GRAB

SUITABLE FOR ALL CONSTRUCTION SITES

EASY APPLICATION

PRODUCT CHARACTERISTICS

Drying time: 5–10 minutes
Open time: 40–45 minutes
Foot traffic: 12 hours
Curing time: 24–48 hours
Coverage: 300–400g/m²





STIX A330 LINO PROJECT ADHESIVE - LINOLEUM

Dispersion adhesive with high initial adhesive force for bonding linoleum, cork linoleum and corkment on absorbent subfloor.

STRONG ADHESION

ODOUR-FREE

/ STIX

LINO

HIGH RETENTION CAPACITY

PRODUCT CHARACTERISTICS

- Waiting time: 5 minutes - Laying time: 10-15 minutes

- Apply pressure to the linoleum again after 30 minutes
- Walk on time: 24 hours
- Coverage: 400g/m²



(1)

EC 1





STIX A710 LINO ECO+ BIOBASED ADHESIVE LINOLEUM

Very low-emission dispersion adhesive for linoleum. Based on renewable raw materials.

FAST INITIAL ADHESION
 ORGANICALLY BASED
 HIGH RETENTION CAPACITY

PRODUCT CHARACTERISTICS

 Waiting time: 10-15 minutes
 Laying time: 10-15 minutes
 Apply pressure to the linoleum again after 30 minutes
 Walk on time: 24 hours

- Coverage: 400-550g/m²







STIX A930 MULTI FASER LTIADHESIVE

Multifunctional, fibre-based dispersion adhesive for PVC coverings (sheets and tiles), LVT design coverings, cushioned vinyl coverings, linoleum, rubber coverings with smooth surface, carpets with different backings as well as coconut and sisal coverings.

GOOD INITIAL ADHESION

SHORT WAITING TIME

HARD ADHESIVE RIB

PRODUCT **CHARACTERISTICS** -

- Waiting time: 5 minutes - Laying time : 20 minutes Apply pressure to the floor covering again after 40 minutes - Walk on time: 24 hours - Coverage: 300-600g/m²



•

EC 1

Ow emis

Boath Gaster Royfstillauses 2-195.19-28

HIGH TACK

STIX P956 2K TWO-COMPONENT POLYURETHANE ADHESIVE FOR FLOOR COVERINGS

Bostik

Two-component polyurethane adhesive for laying floor coverings subjected to heavy-duty use or high mechanical or thermal stress. All soft floor coverings and wood floorings. Suitable for use indoor and outdoor applications as well as in damp premises.

VERY HIGH BONDING PERFORMANCE

MOISTURE AND HEAT RESISTANT

INDOOR - OUTDOOR

PRODUCT CHARACTERISTICS

- Open time: 1 hour - Foot traffic: 24 hours

- Curing time: 48 hours - Coverage: 300-900g/m²





STIX H995 ELASTIC XTREM

1K adhesive for bonding homogeneous PVC coverings, LVT design coverings, cushioned vinyl coverings, linoleum and rubber coverings, especially with increased thermal and mechanical stress and/or increased wet load.

FOR INCREASED LOADS

NOT CLASSIFIED

EXTREME SHEAR STRENGTH

PRODUCT CHARACTERISTICS

- Waiting time: 10 minutes - Laving time : 30 minutes Apply pressure to the floor covering again after 40 minutes - Walk on time: 24 hours
- Coverage: 320-380g/m²



SOFT FLOOR ADHESIVES

STIX A970 ELECTRO CONDUCTIVE ADHESIVE FOR ELIMINATING ELECTROSTATIC LOADS

Adhesive for laying conductive and dissipative floor coverings. Especially suited to premises requiring the elimination of electrostatic loads, such as IT rooms, electronic equipment plants, laboratories, telecommunications centers and hospital facilities.

HIGH GRAB

COMPLETE SYSTEM: TO BE USED WITH CONDUCTIVE PRIMER

FLAWLESS ELECTRICAL CONDUCTIVITY

PRODUCT **CHARACTERISTICS**

- Drying time: 10-15 minutes

- Open time: 40-45 minutes
- Foot traffic: 24 hours
- Curing time: 48-72 hours
- Coverage: 400-550g/m'







FIX A760



Heavy-duty tackifier adhesive for application of all types of removable carpet and vinyl tiles, loose-lay LVT, heterogenous PVC flooring and broadloom carpets. Allows for removal and recycling of carpet tiles. Multipurpose.

ALLOWS FOR SUBSEQUENT REMOVAL AND REPLACEMENT OF THE FLOORING

HIGH-PERFORMANCE, PERMANENT TACKY FILM

ALL TYPES OF ABSORBENT OR NON ABSORBENT SUBFLOORS

PRODUCT

CHARACTERISTICS

- Drying time:
- Normally absorbent subfloors: 45–60 minutes Non-absorbent subfloors: 2–2.5 hours
- Open time: permanent (non-dust)
- Foot traffic: immediately after
- application of the flooring
- Coverage: 60 120g/m





FIX A320 TACK TACKIFIER ADHESIVE FOR REMOVABLE CARPET TILES

Carpet tiles tackifier is suitable for bonding carpet tiles backed with felt, bitumen or non-woven fibre backing. Allows for removal and recycling of carpet tiles. Ideal for office floors.

SPECIFICALLY FOR OFFICE FLOORS

EASY ROLL-ON APPLICATION

REDUCED COVERAGE

PRODUCT CHARACTERISTICS

- Drying time 30–45 minutes

- Open time: permanent
- Foot traffic: immediately after application of the floor covering
 Coverage: 60 – 100g/m²



FIX A305 CLASSIC SPECIAL FIXING CARPET TILES

Special adhesive for locking self-laying carpet tiles with different backings.

OOD SURFACE COVERAGE

ECONOMIC

PRODUCT CHARACTERISTICS

- Drying time 15–30 minutes
- Open time: permanent
- Foot traffic: immediately after application of the floor covering
- Coverage: 70 100g/m²
- Coverage: 70 100g/





This magazine is published by **Bostik Wall & Floor SU** Design and editorial support: RED AGENCY PARIS

KEU AGENC FARIS Photo credits: Bostik - Tarkett – Objectflor – Gerflor – Balsan – Ege – Shutterstock[®] – Getty Images[®] As part of Arkema's sustainable development process, this report is printed on PEFC-certified paper sourced from pulp from responsibly managed forests. The printer has been awarded the imprim Vert® label for compliance with the French printing ndustry's environmental standards.

Bostik S.A. 420 Rue d'Estienne d'Orves 92700 COLOMBES - FRANCE Tél. : +33 (1) 55 99 90 00

www.bostik.com