



VOC DATA SHEET

PRODUCT	PRODUCT NAME		g/Lt	SCAQMD PRODUCT TYPE
30619353	H725 SEAL 'N' FLEX FAÇADE WHITE	290ML	1.80	ARCHITECTURAL SEALANTS
30619349	H725 SEAL 'N'N FLEX FAÇADE BLACK	290ML	1.80	ARCHITECTURAL SEALANTS
30619351	H725 SEAL 'N' FLEX FAÇADE CONCRETE GREY	290ML	1.80	ARCHITECTURAL SEALANTS
30617200	H725 SEAL 'N' FLEX FAÇADE LIGHT BEIGE	290ML	1.80	ARCHITECTURAL SEALANTS
30617480	H725 SEAL 'N' FLEX FAÇADE WHITE	600ML	1.80	ARCHITECTURAL SEALANTS
30619350	H725 SEAL 'N' FLEX FAÇADE BLACK	600ML	1.80	ARCHITECTURAL SEALANTS
30617481	H725 SEAL 'N' FLEX FAÇADE CONCRETE GREY	600ML	1.80	ARCHITECTURAL SEALANTS

03/01/2022

Unless otherwise stated, the TVOC of this product has been calculated theoretically, based on the known VOC values of the individual raw material components. In the event that the VOC level of any individual raw material component is unknown, the TVOC has been determined experimentally using SCAQMD Method 304-91, as referenced by the South Coast Air Quality Management District (SCAQMD) Rule 1168.



Jethro Ramirez
Technical Manager – Asia Pacific

Note: For any further enquires contact Bostik on 613 9279-9333. A VOC level of “0” is a true value. The VOC level of a product which may be available in a range of colours may vary depending on the colour.

Factory: Bostik Australia Pty Ltd, 51-71 High Street, Thomastown Victoria Australia

ABN 79 003 893 838 Tel: 1800 267 845 Fax: 1300 723 688

www.bostik.com.au

A company of ARKEMA