



BOSTIK ROLL

REINFORCED DOUBLE-SIDED ADHESIVE TAPE

TECHNICAL SHEET 03/10/2024

SMART ADVANTAGES

- Solvent-free adhesive tape
- Instant grab
- Clean & easy installation
- Immediate grip and long-life bond
- Extra strong
- Immediate foot traffic
- No wait time required
- Compatible with under-floor heating

DESCRIPTION

Bostik Roll is a high strength adhesive tape that is suitable for the fast installation of soft textile and resilient floor coverings, all types of skirting, capping strips, coving and other floor or lightweight wall mounted accessories. It can be used as a direct alternative to traditional solvent and water-based adhesives.

The double-sided tape is quick, easy and clean to use, offering an instantaneous grab with a pressure sensitive bond. Bostik Roll is solvent-free and does not leave behind vapour often associated with traditional contact adhesives. It will not discolour bonded materials and offers excellent plasticiser migration resistance, making it particularly suited for use with PVC products.

USES

The product is used to bond a wide range of materials such as textile and resilient flooring and lightweight wall accessories to sound and strong substrates.

Bostik Roll is available in multiple sizes, enabling complex applications to be carried out.

As it's solvent-free, Bostik Roll is an environmentally friendly option that has less impact on the building occupants. It achieves A+ and ECI Plus ratings with LEED and EN 13999:2007 for BREEAM, thanks to its very low VOC emissions.



PRODUCT CHARACTERISTICS

Form	Self-adhesive tape
Composition	Pre-coating based on synthetic resins and reinforced weft
Coverage	30607844 - 25mm x 50m
	30607845 - 50mm x 50m
	30607846 - 85mm x 50m
	30607857 - 240mm x 25m
Application temperature	10 to 30°C

PRODUCT PERFORMANCE DATA

Open time	Unlimited
Drying time	Immediate
Walk on time	Immediate
Curing time	Immediate

USING BOSTIK ROLL

Please read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting www.bostik.com.au or by scanning the QR code on relevant packaging.

PREPARATION

- Ensure the substrate is clean, sound, dry and free from contaminants that may hinder adhesion.
- Any contaminants on either the wall or floor that may hinder adhesion, such as grease, dust, wallpaper, silicone sealants, some curing compounds and old adhesive residues should be completely removed.
- Metal, plastic, previously applied adhesives or painted walls will need mechanically abrading to provide a key. If in doubt always carry out a trial to ensure compatibility.
- Ensure any damaged walls or floors are made good and that there is a smooth, flat surface to apply Bostik Roll to.

PRIMING

- Prime textured or porous surfaces as required with Bostik Universal Primer. Dense, compact surfaces should be lightly abraded and made dust free.
- Do not use a solvented, aerosol primer as this can impair adhesion.

APPLICATION

- Ensure that the surface is free from dust. Dust needs to be removed from the surface as it could hinder adhesion properties.
- Allow the skirting and tape to acclimatise to room temperature prior to installation. Heating of skirting is not required.
- Cold temperatures and damp sites can result in a condensate of water on the substrates and materials being applied, which will prevent adhesion. Ideal performance will be achieved in the temperature range +10°C and +30°C.
- Bostik Roll must always be applied to the substrate, i.e. the floor or wall, and not on the floor covering or accessory.
- Once applied to the substrate, the tape should be firmly compressed using a suitable hand roller.
- Prior to removing the release paper, ensure all materials (capping, skirting, vinyl etc.) are cut to the appropriate size.
- Remove the release paper and using controlled, consistent hand pressure, place the materials onto the Bostik Roll avoiding air entrapment. Once firmly in place, roller the materials to enhance the bond.
- Bostik Roll offers an instant pressure sensitive bond enabling further processes to be carried out immediately.

- In areas such as shower enclosures and wet rooms, it is essential that the design ensures water is kept away from the adhesive bond line and where necessary use a bead of suitable sealant.

BOSTIK PRE-TESTED ADHESION TO SUBSTRATE (P.A.T.S.)

Bostik offer a service in which a program has been established to eliminate potential field problems by pretesting Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

IMPORTANT NOTES

- For any application not covered, please contact Bostik Hotline on 1800 BOSTIK (267 845)
- Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

STORAGE & SHELF LIFE

Store for up to 18 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +10°C to +30°C and out of direct sunlight. Protect from frost.

HEALTH & SAFETY

SEE THE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.

For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.

PRODUCT CODES

25mm x 50m (8 Rolls per Carton)	30607844
50mm x 50m (5 Rolls per Carton)	30607845
85mm x 50m (3 Rolls per Carton)	30607846
240mm x 20m (1 Roll per Carton)	30607857

Bostik Australia
51-71 High St, Thomastown
VIC 3041
P: 1800 267 845
www.bostik.com.au

BOSTIK HOTLINE

1800 BOSTIK (267 845)



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers, and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers, or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out-of-date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com.au