



# FIREBAN<sup>®</sup> ACRYLIC

## FIRE RATED ACRYLIC SEALANT

04<sup>th</sup> March 2020

### YOUR SMART ADVANTAGES

- Fire rating for gaps up to 40mm
- Designed for Australian conditions
- Good flexibility joint movement +/- 25%
- One part no mixing required
- Very easy to apply and gives a smooth finish
- Smooth gunnability and tool off finish
- Low odour
- Non-toxic
- Asbestos free
- Priming not normally required
- Water clean up
- Prevents the passage of hot gases
- Paintable after fully cured
- Water resistant after cure
- Excellent adhesion to metal, wood, plasterboard, all masonry, AAC and Hebel
- Acoustic capabilities with a 60 STC\* rating in plasterboard construction
- Available in three colours, white, grey and limestone

### DESCRIPTION

**Bostik Fireban<sup>®</sup> Acrylic** is a single component, non-sag, fire rated acrylic based gunnable sealant. A general-purpose product for construction joints and the sealing of service penetrations in plasterboard, concrete floors and masonry wall constructions. **Bostik Fireban<sup>®</sup> Acrylic** is a gun grade acrylic based sealing compound specifically manufactured for sealing low movement interior joints (up to +/- 25%) in masonry and plasterboard to provide a fire barrier for periods up to 4 hours.

### USES

Installation of fire rated sealant in concrete walls and floors, and plasterboard walls.  
Sealing of gaps around pipes, cables, ducts and services, which penetrate, fire rated walls and floors.  
For vertical and horizontal joints, interior applications requiring acoustic properties or STC rating.  
Perimeter sealing of door and window framing interior.  
Sealing gaps between faced and cladding panels to various building materials.  
For new construction and remedial applications.  
To prevent the spread of fire and smoke through walls and floors.

### PRODUCT CHARACTERISTICS

Colour	White, Grey, Limestone
Appearance	Non sag smooth thixotropic paste
Stain and Colour Change	None
Chemical Resistance	Fair
Max. Joint Movement	+/- 25%
VOC g/Lt	36
Product code	
600ml Sausage/ 20 per Carton - Grey	30615090
600ml Sausage/20 per Carton - L/Stone	30615089
300ml Cartridge/20 per Carton - White	30615088
Chemical Type	One component intumescent acrylic
Max. Joint Width	40mm
Service Temperature	-20°C to +90°C
Application Temperature	+5°C to +35°C
Tool Working Time	15 minutes at 25°C
STC Rating*	60

\*rating dependant on overall wall system configuration

### CLASSIFICATIONS/STANDARDS

Fire resistance when tested in accordance with AS1530.4-2014 and AS4072.1-2005

# BOSTIK FIREBAN®ACRYLIC

## SURFACE PREPARATION

Clean all surfaces by removing foreign matter and contaminants such as oil, dust, grease, frost, water, surface dirt, old sealants, curing and mould release agents and any protective coating. Porous substrates should be cleaned by grinding, saw cutting or blast cleaning (sand or water). Dust, loose particles, etc., should be blown out of joints with oil free compressed air or vacuum cleaned. Non-porous and plastic surfaces should be cleaned by solvent or mechanical means. Cleaning solvents should not be allowed to air dry or evaporate without being wiped with a clean, dry cloth.

## APPLICATION

**Bostik Fireban® Acrylic**, when used as an adhesive or sealant, should be dispensed from either the cartridge or sausage sachet by means of a hand or air operated caulking gun designed for such application (available from Bostik). Cut the cartridge and screw on the supplied nozzle. Having previously cut this to give the required angle and bead size. Place the cartridge in a suitable Bostik extrusion gun and press the trigger. For sausages, a barrel gun is required, which is available from Bostik. Clip the end of the sausage and place complete sausage into the barrel of gun, with pierced end located at the top of the nozzle. Screw top of nozzle and housing on barrel of gun. Using the trigger on the gun extrude product from the sausage. To stop product flow, using the thumb, depress the catch plate mechanism located at the very rear of the gun, directly above the trigger. Install back-up or joint bond breaker material as specified.

Apply **Bostik Fireban® Acrylic** in a continuous operation using positive pressure adequate to properly fill and seal a cavity. Tool Bostik Fireban®Acrylic with sufficient pressure to spread the sealant against the back-up material and onto the joint surfaces. A tool with a concave profile is recommended to achieve the correct shape.

## SURFACE PREPARATION

**Bostik Fireban® Acrylic** should be applied to a minimum depth of 6mm, maximum width of 40mm. The ratio of joints width to sealant depth should be approximately 2:1. Joints width should not be less than 6mm.

The joint must allow a sealant depth, after installation of backer rod or bond breaking material, of a minimum of 6mm. Lap shear joints should have a bead width equal to, or greater than twice the anticipated movement. A conservative design practice, which uses a portion of the sealant's movement capability as a safety factor is recommended. Sealants are subject to cohesive failure when the actual movement is greater than their rated capability.

## COVERAGE

Linear Meters per 600ml sausage (Approx.)

Size	12x6	16x8	20x10	24x12
600ml	8.4	5.0	3.0	2.0

Calculation formula 
$$\frac{W \times D \times L}{1000} = \text{Litres}$$

Litres / 0.6 = No. of 600ml sausages

W = Width (mm) D = Depth (mm) L = Length (metres)

## PRIMING

Priming is not required unless surface to be bonded is in poor condition or exceptionally porous. Consult Bostik Technical department for advice on priming

## MIXING

No mixing is required for **Bostik Fireban® Acrylic**. Simply use directly from sausage or cartridge.

## PAINTABILITY

**Bostik Fireban® Acrylic** is paintable after fully cured

## Important Notes

- **Bostik Fireban® Acrylic** is not recommended for water immersion, exposed external joint sealing or areas subject to heavy traffic.
- **Bostik Fireban® Acrylic** should not be applied with wet tooling techniques. The use of solvents, water or detergent solution is not recommended.
- **Bostik Fireban® Acrylic** should not be applied to surfaces with special protective or cosmetic coatings, without prior consultation with the manufacturer. Such surfaces include, but are not limited to, mirrors, reflective glass, or surfaces coated with Teflon, polyethylene or polypropylene.
- **Bostik Fireban® Acrylic** can be affected by water before or during cure. The sealant should not be stored, applied or cured in areas where unusually high humidity or free water is present during the application or initial cure.
- **Bostik Fireban® Acrylic** should be allowed to cure prior to subjecting to any intermittent water exposure.
- Do not apply to surfaces with temperature under 5°C, as cure will be retarded.

# BOSTIK FIREBAN® ACRYLIC

## BOSTIK CO-OPERATIVE TEST PROGRAM

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

## CURE RATE

The cure rate is dependent on the bead size (width & depth), and is greatly affected by temperature, humidity, and the presence of water and moisture on the substrate. Approximate cure rates at 23°C and 50% RH are as follows;

- 1mm – 1 day
- 3mm – 5 days

## STORAGE & SHELF LIFE

All material shall be stored under cover in a manner that will prevent damage, preferably on pallets and protected from excessive heat and moisture. Do not freeze. **Bostik Fireban® Acrylic** has a shelf life of 18 months from date of manufacture when stored at or below 27°C.

## SAFETY PRECAUTIONS

Refer to the Safety Data Sheet for additional information.  
SDS can be downloaded from [www.bostik.com.au](http://www.bostik.com.au)

## CLEAN UP

Equipment can be easily cleaned with water while wet.

## PACKAGING

**Bostik Fireban® Acrylic** is available in 600ml sausages and 300ml cartridges.

## FIRE

**Bostik Fireban® Acrylic** is non-flammable

## VOC INFORMATION

**36 g/Lt**

**For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.**

BOSTIK HOTLINE

Smart help 1800 267 845



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit [www.bostik.com.au](http://www.bostik.com.au)