

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK P300
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended useBuilding and construction work.

Uses advised against Consumer use.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik BV De Voerman 8 PO Box 303

5215 MH's-Hertogenbosch, The Netherlands

Tel: +31 736 244 244 Fax: +31 736 244 344

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 - (H332) |
|--|---------------------------|
| Skin corrosion/irritation | Category 2 - (H315) |
| Serious eye damage/eye irritation | Category 2 - (H319) |
| Respiratory sensitisation | Category 1 - (H334) |
| Skin sensitisation | Category 1 - (H317) |
| Carcinogenicity | Category 2 - (H351) |
| Effects on or via lactation | Yes - (H362) |
| Specific target organ toxicity — single exposure | Category 3 - (H335) |
| Specific target organ toxicity — repeated exposure | Category 2 - (H373) |
| Chronic aquatic toxicity | Category 4 - (H413) |
| Aerosols | Category 1 - (H222, H229) |

2.2. Label elements

Contains Isocyanic acid, polymethylenepolyphenylene ester, Alkanes, C14-17, chloro

Europe - EN Page 1/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1



Signal word Danger

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H362 - May cause harm to breast-fed children.

H373 - May cause damage to organs through prolonged or repeated exposure.

H413 - May cause long lasting harmful effects to aquatic life.

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P260 - Do not breathe mist/vapours/spray

P263 - Avoid contact during pregnancy/while nursing

P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P405 - Store locked up

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

Special provisions concerning the labelling of certain mixtures

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. Type A1 according to standard EN 14387) is used. Reserved for industrial and professional use.

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. During

Europe - EN Page 2/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

transportation by car the cans should stand upright in the cargo space. The mentioned hazards are valid for the non-reacted content of the can or of the fresh foam. When foaming the propellants are highly flammable.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

| Chemical name | EC No | CAS No | Weight-% | Classification according to Regulation (EC) No. 1272/2008 [CLP] | Specific concentration limit (SCL) | REACH registration number |
|---|-----------|------------|-----------|--|--|---------------------------------|
| Isocyanic acid, polymethylenepolypheny lene ester | 618-498-9 | 9016-87-9 | >25 - <40 | STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332) | STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1% | [7] |
| Alkanes, C14-17, chloro | 287-477-0 | 85535-85-9 | 20 - 25 | Lact. (H362) (H362) (EUH066) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) | | 01-2119519269- 33-XXXX |
| Dimethyl ether | 204-065-8 | 115-10-6 | 5 - <10 | Flam. Gas 1 (H220) Press. Gas | | 01-2119472128- 37-XXXX |

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

Europe - EN Page 3/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Inhalation Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped,

give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical

advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes. Do

not use solvents or thinners to dissolve the material.

Ingestion May produce an allergic reaction. Do NOT induce vomiting. Clean mouth with water and

drink afterwards plenty of water. Never give anything by mouth to an unconscious

person. Get immediate medical advice/attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as

required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/

or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Burning sensation. Difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Product is or contains a sensitiser. May cause sensitisation by inhalation and skin contact. May cause sensitisation by skin

contact.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

Hydrogen cyanide. Isocyanates.

5.3. Advice for firefighters

Europe - EN Page 4/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

Special protective equipment for Firefighters should wear so

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take

precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without

risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sectionsSee section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other

ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off

contaminated clothing and wash it before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside,

before re-use.

Europe - EN Page 5/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition

(i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep out of the reach of children.

Keep from freezing.

7.3. Specific end use(s)

Specific use(s)

Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

| Chemical name | European Union |
|----------------|-----------------------------|
| Dimethyl ether | TWA: 1000 ppm |
| 115-10-6 | TWA: 1920 mg/m ³ |

Derived No Effect Level (DNEL) No information available

| Derived No Effect Level (DNEL) | | | | |
|--|----------------|--------------------------------|---------------|--|
| Alkanes, C14-17, chloro (855 | 535-85-9) | | | |
| Туре | Exposure route | Derived No Effect Level (DNEL) | Safety factor | |
| worker Long term Systemic health effects | Inhalation | 6.7 mg/m³ | | |
| worker Systemic health effects Long term | Dermal | 47.9 mg/kg bw/d | | |

| Dimethyl ether (115-10-6) | | | |
|---------------------------|------------|------------|---------------|
| Туре | | | Safety factor |
| | | (DNEL) | |
| worker | Inhalation | 1894 mg/m³ | |
| Long term | | | |
| Systemic health effects | | | |

| Derived No Effect Level (DNEL) | | | | |
|--|----------------|--------------------------------|---------------|--|
| Alkanes, C14-17, chloro (85535-85-9) | | | | |
| Туре | Exposure route | Derived No Effect Level (DNEL) | Safety factor | |
| Consumer Long term Systemic health effects | Inhalation | 2 mg/m³ | | |
| Consumer | Dermal | 28.75 mg/kg bw/d | | |

Europe - EN Page 6/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

| Long term Systemic health effects | | | |
|-----------------------------------|------|-----------------|--|
| Consumer | Oral | 0.58 mg/kg bw/d | |
| Long term Systemic health effects | | | |

| Dimethyl ether (115-10-6) | | | |
|---------------------------|----------------|-------------------------|---------------|
| Туре | Exposure route | Derived No Effect Level | Safety factor |
| | - | (DNEL) | - |
| Consumer | Inhalation | 471 mg/m³ | |
| Long term | | | |
| Systemic health effects | | | |

Predicted No Effect Concentration No information available. **(PNEC)**

| Predicted No Effect Concentration (PNEC) | |
|--|--|
| Alkanes, C14-17, chloro (85535-85-9) | |
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Freshwater | 1 μg/l |
| Marine water | 0.2 μg/l |
| Microorganisms in sewage treatment | 80 mg/l |
| Freshwater sediment | 13 mg/kg dry weight |
| Marine sediment | 2.6 mg/kg dry weight |
| Soil | 11.9 mg/kg dry weight |

| Dimethyl ether (115-10-6) | |
|------------------------------------|--|
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Freshwater | 0.155 mg/l |
| Marine water | 0.016 mg/l |
| Microorganisms in sewage treatment | 160 mg/l |
| Freshwater sediment | 0.681 mg/kg dry weight |
| Soil | 0.45 mg/kg dry weight |

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the

gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min.

Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

Wear appropriate personal protective clothing to prevent skin contact. In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases

and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearanceFoamColourYellow

Europe - EN Page 7/15

BOSTIK P300 Revision date 12-Feb-2021

Supercedes Date: 12-Feb-2021 Revision Number 1

Not applicable, Aerosol

bar @ 23 °C

Odour Characteristic Slight

Property Values Remarks • Method

No information available

pH No data available

Melting point / freezing point No data available
Initial boiling point and boiling Not applicable, Aerosol . Not applicable, Aerosol

range

Odour threshold

Flash point Not applicable, Aerosol .

Evaporation rate

No data available

Flammability Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive 18.6 Vol.%

limits

Lower flammability or explosive 1.7 Vol.%

limits

Vapour pressure 6-7

Relative vapour density No data available Relative density No data available Immiscible in water Water solubility Solubility(ies) No data available **Partition coefficient** No data available No data available °C **Autoignition temperature Decomposition temperature** No data available Kinematic viscosity No data available Dynamic viscosity No data available

Dynamic viscosity

Explosive properties

Oxidising properties

No data available
No data available
No data available

9.2. Other information

Solid content (%)

VOC Content (%)

No information available

No information available

Liquid Density 0.95 g/cm³

Minimum Ignition Temperature (°C) 235

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat. Do not freeze. Protect from moisture.

10.5. Incompatible materials

Europe - EN Page 8/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Water. Alcohols. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Hydrogen cyanide. Carbon monoxide. Carbon dioxide (CO2). Hydrogen chloride.

Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of

respiratory tract. Harmful by inhalation.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged

skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional

affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing,

tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause

redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 11,940.30 mg/kg ATEmix (inhalation-dust/mist) 3.28 mg/l

ATEmix (inhalation-dust/mist) 3.28 mg/l ATEmix (inhalation-vapour) 24.10 mg/l

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|-----------------------------|---|--------------------------|
| Isocyanic acid, polymethylenepolyphenylene | LD50 > 10000 mg/kg (Rattus) | LD 50 > 9400 mg/kg (Oryctolagus cuniculus) | =1.5 mg/L (Rattus) 4 h |
| ester 9016-87-9 | | , | |
| Alkanes, C14-17, chloro 85535-85-9 | >4000 mg/kg (Rattus) | > 2000 mg/kg (Rattus) | |
| Dimethyl ether 115-10-6 | | | =164000 ppm (Rattus) 4 h |

Europe - EN Page 9/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

Reproductive toxicity Classification based on data available for ingredients. May cause harm to breast-fed

children.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

| Chemical name | European Union |
|-------------------------|----------------|
| Alkanes, C14-17, chloro | Lact. |
| 85535-85-9 | |

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity May cause long lasting harmful effects to aquatic life.

| Chemical name | Algae/aquatic | Fish | Toxicity to | Crustacea | M-Factor | M-Factor |
|-----------------------|---------------|---------------|----------------|---------------|----------|-------------|
| | plants | | microorganisms | | | (long-term) |
| Isocyanic acid, | ErC50 (72h) | CL50 (96h) | - | EC50 (24H) | | |
| polymethylenepolyphen | >1640 mg/L | >1000 mg/L | | >1000 mg/L | | |
| ylene ester | Algae | (Danio rerio) | | Daphnia magna | | |

Europe - EN Page 10/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

| 9016-87-9 | (scenedesmus subspicatus) (OECD 201) | | | | |
|--|--|--|---|---|----|
| Alkanes, C14-17, chloro 85535-85-9 | - | LC50: >500mg/L (48h, Leuciscus idus) | - | EC50 (48h) = 0.0059 mg/l (Daphnia magna) OECD 202 | 10 |
| Dimethyl ether 115-10-6 | - | LC50: >4.1g/L (96h, Poecilia reticulata) | - | > 4400 mg/L (Daphnia) (NEN 6501) | |

12.2. Persistence and degradability

Persistence and degradability No information available.

| Component Information | | | | |
|--|---------------|-------------------|---------------------------|--|
| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | | | | |
| Method | Exposure time | Value | Results | |
| OECD Test No. 302C: Inherent | 28 days | 0% biodegradation | Not readily biodegradable | |
| Biodegradability: Modified MITI Test | - | | | |
| (II) | | | | |

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

| Chemical name | Partition coefficient | Bioconcentration factor (BCF) |
|----------------------------------|-----------------------|-------------------------------|
| Isocyanic acid, | - | < 14 |
| polymethylenepolyphenylene ester | | |
| 9016-87-9 | | |
| Alkanes, C14-17, chloro | 6 | - |
| 85535-85-9 | | |
| Dimethyl ether | -0.18 | - |
| 115-10-6 | | |

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB. .

| Chemical name | PBT and vPvB assessment |
|---------------------------------------|---------------------------------|
| Alkanes, C14-17, chloro 85535-85-9 | The substance is not PBT / vPvB |
| Dimethyl ether 115-10-6 | The substance is not PBT / vPvB |

12.6. Other adverse effects

Other adverse effects No information available.

Endocrine Disruptor Information

| Chemical name | EU - Endocrine Disrupters | EU - Endocrine Disruptors - | |
|---------------|---------------------------|-----------------------------|--|
| | Candidate List | Evaluated Substances | |

Europe - EN Page 11/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 **Revision Number 1**

Alkanes, C14-17, chloro Group III Chemical

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Empty containers should be taken to an approved waste handling site for recycling or Contaminated packaging

disposal.

according to EWC / AVV

Waste codes / waste designations 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product

was used.

08 05 01* waste isocyanates **European Waste Catalogue**

16 05 04* gases in pressure containers (including halons) containing dangerous

substances

17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03

15 01 04 metallic packaging

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to Note:

shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Keep from freezing.

Land transport (ADR/RID)

UN1950 14.1 UN number or ID number 14.2 Proper Shipping Name Aerosols 14.3 Transport hazard class(es) 2 2.1 Labels

14.4 Packing group Not regulated

Description UN1950, Aerosols, 2, (E), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special Provisions 327, 625, 344, 190

Classification code 5A **Tunnel restriction code** (E) Limited Quantity (LQ) 1 L

IMDG

14.1 UN number or ID number UN1950

14.2 Proper Shipping Name Aerosols (Alkanes, C14-17, chloro)

14.3 Transport hazard class(es)

14.4 Packing group Not regulated

UN1950, Aerosols (Alkanes, C14-17, chloro), 2.1, (0°C c.c.), Marine Pollutant Description

14.5 Marine pollutant

14.6 Special Provisions 63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ) See SP277 **EmS-No** F-D, S-U

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

Europe - EN Page 12/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

14.1 UN number or ID number UN1950

14.2 Proper Shipping Name Aerosols, flammable

14.3 Transport hazard class(es) 2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, flammable, 2.1

14.5 Environmental hazards Yes

14.6 Special Provisions A145, A167, A802

Limited Quantity (LQ) 30 kg G ERG Code 10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS P3b - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Europe - EN Page 13/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

| Chemical name | French RG number |
|--|------------------|
| Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9 | RG 62 |
| Dimethyl ether 115-10-6 | RG 84 |

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

| Chemical name | Netherlands - List of Carcinogens |
|-------------------------|-----------------------------------|
| Alkanes, C14-17, chloro | Can be harmful via breastfeeding |
| 85535-85-9 | |

<u>Denmark</u>

Norway

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H220 - Extremely flammable gas

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation H351 - Suspected of causing cancer

H362 - May cause harm to breast-fed children

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Europe - EN Page 14/15

BOSTIK P300 Revision date 12-Feb-2021 Supercedes Date: 12-Feb-2021 Revision Number 1

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 12-Feb-2021

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Europe - EN Page 15/15