

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019

Revision date 11-May-2020 Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK RENO P520 EASY - PART B

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work. Joint sealants. Restricted to professional users.

Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik GmbH An der Bundesstrasse 16 33829 Borgholzhausen, Germany Tel: +49 (0) 5425 / 801 0

Fax: +49 (0) 5425 / 801 140

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

treland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)

2.2. Label Elements

Contains: Isocyanic acid, polymethylenepolyphenylene ester



Signal word DANGER

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019 Revision Number 1.01

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eve irritation.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction.

Precautionary statements

P260 - Do not breathe mist/vapours/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P402 + P404 - Store in a dry place. Store in a closed container.

P501 - Dispose of contents/ container to an approved waste disposal plant.

Additional information

Please refer also to Safety Data Sheet of Part A.

Reserved for industrial and professional use.

2.3. Other Hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Isocyanic acid, polymethylenepolypheny lene ester	618-498-9	9016-87-9	80 - 100	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	[7]

Revision date 11-May-2020

BOSTIK RENO P520 EASY - PART B
Supercedes Date: 30-Oct-2019
Revision date 11-May-2020
Revision Number 1.01

|--|

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. IF exposed or

concerned: Get medical advice/attention.

Inhalation Remove to fresh air. Get immediate medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do.

Continue rinsing. Consult an ophthalmologist.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. In the case

of skin irritation or allergic reactions see a doctor.

Ingestion Do NOT induce vomiting. Clean mouth with water. Drink 1 or 2 glasses of water. Never

give anything by mouth to an unconscious person. Get immediate medical

advice/attention.

Self-protection of the first aider Avoid breathing vapours or mists. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/

or wheezing. Itching. Rashes. Hives. Burning sensation. Difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Delayed pulmonary edema may occur. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the Thermal decomposition can lead to release of irritating and toxic gases and vapours.

chemical

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Hydrogen cyanide. Nitrogen oxides (NOx).

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019 **Revision Number** 1.01

5.3. Advice for firefighters

Special protective equipment for Wear self contained breathing apparatus for fire fighting if necessary.

Revision date 11-May-2020

fire-fighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Do not breathe vapour or mist. Use personal protective

equipment as required. Avoid contact with skin, eyes or clothing.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent product from entering drains. Do not allow to enter into soil/subsoil. **Environmental precautions**

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product

and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use with local exhaust ventilation. Do not breathe vapour

or mist. Use personal protection equipment. Avoid contact with skin, eyes or clothing.

Please refer also to Safety Data Sheet of Part A.

Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when **General hygiene considerations**

using this product. Wash hands before breaks and after work. Take off all contaminated

clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Protect from moisture. Keep containers tightly closed in a dry, cool and well-ventilated **Storage Conditions**

place. Keep at temperatures between 10 and 30 °C.

7.3. Specific end use(s)

Specific Use(s)

Building and construction work. Joint sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

BOSTIK RENO P520 EASY - PART B
Supercedes Date: 30-Oct-2019
Revision Aumber 1.01

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing

Chemical name	European Union	Ireland	United Kingdom
Isocyanic acid,	-	-	TWA: 0.02 mg/m ³
polymethylenepolyphenylene ester			STEL: 0.07 mg/m ³ SEN; as -NCO
9016-87-9			
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m ³	TWA: 260 mg/m ³	TWA: 266 mg/m ³
	*	STEL: 600 ppm	STEL: 250 ppm
		STEL: 780 mg/m ³	STEL: 333 mg/m ³
		Sk*	Sk*

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available. **(PNEC)**

8.2. Exposure controls

Engineering controls Vapours/aerosols must be exhausted directly at the point of origin.

Personal Protective Equipment

Eve/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Gloves must conform to standard EN 374. Recommended Use:.

Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Unsuitable gloves

materials:. Disposable gloves. Leather.

Skin and body protection Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation wear respiratory protection. During spraying wear

suitable respiratory equipment. Wear a respirator conforming to EN 140 with Type A/P2

filter or better.

Recommended filter type: Brown, White.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available

ColourBrownOdourEarthy Musty

Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point / freezing point No data available

Boiling point / boiling range
Flash point

No data available
> 200 °C

Flash point > 200 °C DIN EN ISO 2719
Evaporation rate No data available

Flammability (solid, gas)

Flammability Limit in Air

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019 Revision Number 1.01

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableVapour densityNo data available

Relative density 1.10 - 1.15 @ 23 °C

Water solubility Reacts with water Solubility(ies) No data available Partition coefficient No data available Autoignition temperature No data available Decomposition temperature No data available

Kinematic viscosity

No data available

Dynamic viscosity approx. 150 - 250 mPa s ISO 2884-1

Explosive properties No data available Oxidising properties No data available

9.2. Other information

Solid content (%) No information available VOC Content (%) No information available

Density 1.10 - 1.15

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Do not get water inside containers: a violent reaction may occur. None under normal

processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Heat.

10.5. Incompatible materials

Incompatible materials Amines. Alcohols. Water. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decompositionNone under normal use conditions. Stable under recommended storage conditions.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Revision date 11-May-2020

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019

Product Information

Inhalation Harmful by inhalation. May cause allergy or asthma symptoms or breathing difficulties if

nhaled.

Eye contact Causes serious eye irritation.

Skin contact Causes skin irritation. May cause sensitisation by skin contact.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document ATEmix (inhalation-dust/mist) 1.50 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isocyanic acid,	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg	=1.5 mg/L (Rattus) 4 h
polymethylenepolyphenylene		(Oryctolagus cuniculus)	-
ester			
9016-87-9			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Component Information						
Isocyanic acid, polymethy	Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 404:	Rabbit				Mild skin irritant	
Acute Dermal						
Irritation/Corrosion						

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause an allergic skin reaction.

Component Information			
Isocyanic acid, polymethylenepolypl	nenylene ester (9016-87-9)		
Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		No sensitisation responses
Sensitisation			were observed
OECD Test No. 429: Skin	Mouse		sensitising
Sensitisation: Local Lymph Node			
Assay			

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Revision date 11-May-2020

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019

Revision date 11-May-2020 Revision Number 1.01

Carcinogenicity Contains a known or suspected carcinogen.

Component Information				
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)				
Method	Species	Results		
OECD Test No. 453: Combined Chronic	Rat	Carcinogenic		
Toxicity/Carcinogenicity Studies				

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity .

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		Micro-organisms			(long-term)
Isocyanic acid,	ErC50 (72h)	CL50 (96h)	-	EC50 (24H)		
polymethylenepolyphen	>1640 mg/L	>1000 mg/L		>1000 mg/L		
ylene ester	Algae	(Danio rerio)		Daphnia magna		
9016-87-9	(scenedesmus					
	subspicatus)					
	(OECD 201)					

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information				
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)				
Method	Exposure time	Value	Results	
OECD Test No. 302C: Inherent	28 days	0% biodegradation	Not readily biodegradable	
Biodegradability: Modified MITI Test	-	<u> </u>		
(II)				

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Isocyanic acid,	-	< 14
polymethylenepolyphenylene ester 9016-87-9		

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or

vPvB.

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1UN NumberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing GroupNot regulated14.5Environmental hazardsNot applicable14.6Special ProvisionsNone

IMDG

14.1 UN numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Marine PollutantNp

14.5 Marine Pollutant Np
14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Revision date 11-May-2020

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents

at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H335 - May cause respiratory irritation

H373 - May cause damage to organs through prolonged or repeated exposure

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer

H332 - Harmful if inhaled

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

Revision date 11-May-2020

BOSTIK RENO P520 EASY - PART B

Supercedes Date: 30-Oct-2019

vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 11-May-2020

Indication of changes

Revision note SDS sections updated, 1, 3, 16.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Revision date 11-May-2020