

H780

SUPERGRIP INVISIBLE UNIVERSAL CRYSTAL CLEAR ADHESIVE

TECHNICAL DATA SHEET

BENEFITS

- Universal crystal clear adhesive
- Free of isocyanates and solvents
- No shrinkage, bubble free curing
- Adheres perfectly without primer to most surfaces
- Neutral curing, almost odourless
- Non corrosive towards metals
 High mechanical resistance strength and E-modulus

PRODUCT DESCRIPTION

Bostik H780 SUPERGRIP INVISIBLE is an universal high strength crystal clear hybrid adhesive.

APPLICATIONS

Bostik H780 SUPERGRIP INVISIBLE was specifically developed as a universal powerful construction adhesive. **Bostik H780 SUPERGRIP INVISIBLE** is due to its special formulation also suitable for areas that can come in contact with food / where food is being processed / stored. Bostik recommends to use the product for interior use as it might discolour.

DIRECTIONS OF USE

Apply adhesive in a 'ventilating' way in vertical stripes with 10 - 20 cm distance between stripes. Do not apply the adhesive in dots! Use 3 mm thick double sided tape to support adhesion during the first 24 hours, and to make sure that the thickness of the adhesive is correct.



TECHNICAL DATA		
100% modulus	DIN 53504 S2	1,15 N/mm ²
Application rate	@ Ø 2,5 mm/6,3 bar	150-300 g/min
Application		+5°C to + 40°C
temperature		
Base		Hybrid
Curing time	@ +23°C/50% RH	2-3 mm/24 hours
Density	ISO 1183-1	1,06 g/ml
Elongation at break	DIN 53504 S2	450%
Flow	ISO 7390	< 2 mm
Frost resistance		Up to - 15°C
during		
transportation		
Shore A hardness	DIN 53505	45
Skin formation	DBTM 10.00	10 min. @ +23°C/50%
		RH
Temperature		-40°C to +90°C
resistance		
Tensile strength	DIN 53504 S2	3,20 N/mm ²

These values are typical properties and may vary +/-3%

LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for continuous exposure to water
- With prolonged exposure to UV radiation, products can discolour and become less UV stable
- Not suitable for movement and glazing joints
- Not suitable for natural stone and mirrors

SURFACE PREPARATIONS AND FINISHING

Application temperature + 5°C to + 40°C (environment and substrate). Surfaces must be dry, clean and solid. Clean surfaces with **Bostik T100 UNIVERSAL CLEANER**. **Bostik H780 SUPERGRIP INVISIBLE** adheres perfectly without the use of primer to most non porous substrates. Always test adhesion prior to application.

CLEANING

Uncured material and tools can be cleaned by using **Bostik T100 UNIVERSAL CLEANER**. Cured material can only be mechanically removed. Hands can be cleaned with **Bostik T150 CLEANING WIPES.**

COLOUR(S)

- Crystal Clear

PACKAGING

290 ml Cartridge, 12 per box

For product specifications, please refer to the Online Product Detail Page

SHELF LIFE

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 18 months from production date, stored in a dry place.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via the websites.

CERTIFICATIONS

- ISEGA
- EMICODE EC2
- EN 15651-1: F-INT
- A+ French VOC Regulation

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is publicad and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

BOSTIK SMART SUPPORT Smart help digital Bostik.com/ Smart help +971 4 875 1700

Bostik Consumer & Construction

Arkema Middle East DMCC Unit 1108, JBC3 Tower Cluster Y Jumeirah Lakes Towers Dubai, United Arab Emirates Tel.: +971 4 875 1700 www.bostik.com

Bostik Sealing & Bonding Technical Data Sheet H780 SUPERGRIPINVISIBLE_032021