



# H975

## PANELTACK HM

### PROFESSIONAL HIGH MODULES ELASTIC CLADDING PANEL ADHESIVE

#### TECHNICAL DATA SHEET

##### BENEFITS

- Suitable for all sort of cladding panels like fibre cement boards and aluminium composite panels
- Strong, high modulus
- Solvent- and isocyanate-free
- Long-lasting high elasticity with optimum distribution of strain
- Excellent mechanical strength
- Good moisture- and weather-resistance
- Simple and fast fixation

##### PRODUCT DESCRIPTION

**Bostik H975 PANELTACK HM** (High Modulus) is a moisture-curing, elastic adhesive with high modulus based on SMP, specially developed for bonding fibre-cement boards, natural stone and aluminium composite cladding panels.

##### APPLICATIONS

**Bostik H975 PANELTACK HM** has been specially developed as a Bonding of cladding panels for façade cladding, fascias, soffits, canopies and parapets.

##### DIRECTIONS OF USE

See 'Method of use for the bonding of exterior wall cladding panels'. A wide variety of wall cladding panel systems are available on the market, each with their own individual characteristics. Bostik therefore works closely with major wall cladding panel manufacturers to closely match the adhesive system to the specific cladding panels. A detailed Technical Information Sheet is available for a number of cladding panels, with specific information for the cladding panel concerned.



##### TECHNICAL DATA

Application temperature		+5°C to +30°C
Base		Hybrid
Density	ISO 1183-1	1,50 g/ml
Flow	ISO 7390	0 mm
Shore A hardness	DIN 53505	52
Shear strength	ISO 37	2,50 N/mm <sup>2</sup>
Skin formation	DBTM 10.00	15 min. @ +23°C/50% RH
Temperature resistance		-40°C to +90°C
Tensile strength	ISO 37	2,60 N/mm <sup>2</sup>

*These values are typical properties and may vary +/-3%*

##### LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for continuous exposure to water
- Not suitable for movement joints

## SURFACE PREPARATIONS AND FINISHING

See 'Method of use for the bonding of exterior wall cladding panels'. A wide variety of wall cladding panel systems are available on the market, each with their own individual characteristics. Bostik therefore works closely with major wall cladding panel manufacturers to closely match the adhesive system to the specific cladding panels. A detailed Technical Information Sheet is available for a number of cladding panels, with specific information for the cladding panel concerned.

## CLEANING

Uncured material and tools can be cleaned by using Bostik Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Bostik Wipes.

## COLOUR(S)

- Black

## PACKAGING

- 290 ml Cartridge, 12 per box
- 600 ml Sausage, 12 per box

*For product specifications, please refer to the Online Product Detail Page*

## SHELF LIFE

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 12 months from production date, stored in a dry place.


## HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via the websites.

## CERTIFICATIONS

- KOMO

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce



**BOSTIK SMART SUPPORT**

Smart help digital  
[Bostik.com/](https://www.bostik.com/)

Smart help  
**+971 4 875 1700**

## Bostik Consumer & Construction

Arkema Middle East DMCC Unit 1108, JBC3 Tower Cluster Y Jumeirah Lakes Towers Dubai, United Arab Emirates  
Tel.: +971 4 875 1700  
[www.bostik.com](http://www.bostik.com)