

## FIX A320 TACK

TACKIFIER ADHESIVE FOR REMOVABLE CARPET TILES

### KEY BENEFITS

- Specially for office floors
- Easy roll-on application
- Low consumption
- Suitable for all types of removable textile sealing slabs



### APPLICATIONS

#### DESCRIPTION

FIX A320 TACK is an anti-slip fixing device allowing the replacement of removable textile sealing slabs with felt, bitumen or non-woven fabric backing.

#### DESTINATION

##### Areas of applications :

- Concrete paving and flooring
- Traditional cement screed
- Cement or anhydrite fluid screed
- Raised Technical floor
- Chipboard, plywood, OSB3 panels
- Old strip flooring
- Tiling
- Old semi-flexible non-asbestos slab
- Underfloor heating

### PRODUCT CHARACTERISTICS

<b>Composition / colour</b>	Acrylic water based/ white
<b>Waiting time*</b>	30 to 45 minutes
<b>Coverage</b>	60-100g/m <sup>2</sup>
<b>Application temperature</b>	10 to 25°C

\*these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

## SUBFLOOR PREPARATION

### CLEANING PREPARATION

They must be strong, healthy, dry, clean, dust-free, flat and free of fatty products.

For cement-based substrates and calcium sulphate screeds, check that the moisture content of the substrate complies with local regulation before laying, using a carbide spray.

If cement-based substrates do not have the required moisture content, use our HYTEC E336 XTREM moisture barrier.

For other type of substrates, you need to prepare it in accordance with local regulation.

### METHOD OF USE

Apply the fixative with a 12mm anti-drip roller at a rate of :

Areas of applications :	Consumption :
Substrate with an normal absorption	80 to 100 gr/m <sup>2</sup>
Plywood, chipboard and OSB 3	60 to 80 gr/m <sup>2</sup>

Respect a drying time of 30 minutes minimum to obtain the permanent tackifying effect and to allow the subsequent removal of the sealing tiles.

Tighten the slabs and press them tightly.  
Opening to traffic is immediate

## COVERAGE

From 60 to 100g/m<sup>2</sup> depending on the type of coating and the spatula used.

## STORAGE STABILITY

Up to 12 months in the original, unopened container, stored at +10°C and +30°C.

## CLEANING

Tools and fresh traces will be cleaned with clean water.

For sticky products or to strip the glued surfaces, contact us.

Code	UC	PCB	GENCOD
30615735	15 kg	1	3549212484958

## SAFETY

For more details, consult the safety data sheet on <https://bostiksd.thevercs.com/default.aspx>

*The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the pat*

## BOSTIK SMART SUPPORT

Smart help  
+971 4 875 1700



### Bostik Consumer & Construction

Arkema Middle East DMCC, Unit 1108, JBC3 Tower Cluster Y, Jumeirah Lakes Towers Dubai, United Arab Emirates  
Tel.: +971 4 875 1700  
www.bostik.com