

GRIP A310 PROJECT

READY-TO-USE WATER-BASED PRIMER

KEY BENEFITS

- Facilitates application of smoothing compounds
- Ready-to-use
- Quick drying
- Odour free : can be used everywhere, even in occupied premises



APPLICATIONS

DESCRIPTION

GRIP A310 PROJECT is a water-based adhesion primer for new work on absorbent surfaces. Internal floors and walls.

DESTINATION

Ready to use, this primer is designed to secure and develop the adhesion of the self-levelling compounds on subfloors or substrates.

Areas of application :

SUBFLOORS :

- Absorbent and normally absorbent concrete
- Fluid or traditional cement screed
- Anhydrite screed*

WALLS :

- Plaster boards
- Plaster coatings
- Tile bricks

PRODUCT CHARACTERISTICS

Composition / colour	Water-based solution / white translucent
Application temperature	10 to 25°C
Curing time* / Floor installation	30-60min
Coverage	100-150 g/m ²

*these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

SUBFLOOR PREPARATION

CLEANING PREPARATION

Preparation should be in accordance with building standards. Subfloors must be sound, of adequate tensile and compressive strength; free from laitance, cracks and structural defects; clean and free from dust, grease, curing compounds, sealers or any other contaminants that would inhibit proper bond.

Substrate residual moisture content must be evaluated, and in accordance to local building standards and floor manufacturers recommendations.

Adhesive residues that are hard, sound and water-tight should be mechanically cut-back to a minimum.

Soft and weak adhesive residues, paint, and gypsum residues should be completely removed.

Substrate moisture content during application must not exceed 3%. If not, they should be primed with a Moisture Vapour Barrier coating previously to self-levelling installation.

METHOD OF USE

Apply GRIP A310 PROJECT primer evenly in a thin coat using a foam or short-pile roller (coverage: approx. 100 to 150 g/m² per coat). Do not over apply and avoid puddle formation.

Allow to dry for approx. 30 to 60 minutes. Several subsequent layers may be necessary to completely impregnate the substrate. After the primer has dried completely, over-coat with self-levelling compounds (drying time depending on the substrate absorbency, humidity, temperature conditions and quantity of the primer applied).

COVERAGE

From 100 to 150 g/m²/laying

STORAGE STABILITY

Up to 12 months in the original unopened container stored between +10°C and +30°C

CLEANING

Clean tools and fresh spillages with water

Code	UC	PCB	GENCOD
30615709	20 kg	1	3549212484880

SAFETY

For more details, consult the safety data sheet on <https://bostiksd.thevercs.com/default.aspx>

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the pat

BOSTIK SMART SUPPORT

Smart help
+971 4 875 1700



Bostik Consumer & Construction

Arkema Middle East DMCC, Unit 1108, JBC3 Tower Cluster Y, Jumeirah Lakes Towers, Dubai, United Arab Emirates

Tel.: +971 4 875 1700

www.bostik.com