

GRIP X910 FILL & WOOD

SPECIAL 2K PRIMER FOR RENOVATION ON WOODEN SURFACES AND CERAMIC TILES

KEY BENEFITS

- Very high resistance and flexibility
- All wood surfaces and joint filling
- Quick drying
- Easy to use and apply
- Odorless: can be used in all types of locations



APPLICATIONS

DESCRIPTION

GRIP X910 FILL & WOOD is a two-component adhesion primer for preparing and patching old wood flooring and wood panels before applying a fibre-reinforced smoothing compound. Other possible uses : old ceramic tiles and old semi-flexible tiles.

DESTINATION

Complies with all types of locations, even those occupied or open to the public.

Before the application of one of our flexible leveling compounds reinforced with synthetic fibers.

For interior use only.

Areas of application :

- Wooden floorboards, parquet, timber
- CTB-H/CTB-X/OSB-3 wood based panels
- Particleboards and plywood
- Filler fixing and strengthener for joints and wooden floor defects
- Cement screed

PRODUCT CHARACTERISTICS

Composition / colour	Water-based solution + cement / brown
Application temperature	10 to 25°C
Working time*	1h
Walk on time*	2h
Curing time* / Floor installation	4h
Coverage	800 to 1000 g/m ²

*these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

SUBFLOOR PREPARATION

CLEANING PREPARATION

Preparation should be in accordance with building standards. Subfloors must be sound, of adequate tensile and compressive strength; free from laitance, cracks and structural defects; clean and free from dust, grease, curing compounds, sealers or any other contaminants that would inhibit proper bond.

Substrate residual moisture content must be evaluated, and in accordance to local building standards and floor manufacturers recommendations.

Adhesive residues that are hard, sound and water-tight should be mechanically cut-back to a minimum.

Soft and weak adhesive residues and smoothing underlayment should be completely removed.

Residual moisture content of wooden floors must be between 7 and 11%.

Ensure sufficient ventilation of wooden floors. For parquet, fill the joints between planks, then apply primer in a single work step.

METHOD OF USE

Mix the entire kit in a clean container until an even, dark brown color is achieved. Use an electric drill and mixing paddle (< 500 rpm).

Apply the primer evenly with a float. Allow to dry for approx. 4 hours (depending on the substrate, ventilation, humidity and temperature conditions).

Only perform subsequent work after complete drying. If in doubt, delay.

Smoothing and levelling underlayment should be applied after approx. 4 hours.

COVERAGE

800 to 1000 g/m² according the subfloor aspect

STORAGE STABILITY

Up to 12 months in the original, unopened container, stored at +5°C and +30°.

REMARK

Underfloor heating systems must comply with current building regulations. Turn off the heating 48 hours before starting the work. The heating should be turned up to its operating temperatures gradually, in stages over 48 hours after laying the floor covering. Do not apply when underfloor heating is in operation. In all cases, always observe the drying time.

CLEANING

Clean tools and fresh spillages with water.

Code	UC	PCB	GENCOD
30615726	14.5 kg	1	3549212484941

SAFETY

For more details, consult the safety data sheet on <https://bostiksd.thevercs.com/default.aspx>

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

BOSTIK SMART SUPPORT

Smart help
+971 4 875 1700



Bostik Consumer & Construction

Arkema Middle East DMCC, Unit 1108, JBC3 Tower Cluster Y, Jumeirah Lakes Towers Dubai, United Arab Emirates

Tel.: +971 4 875 1700

www.bostik.com