



BOSTIK

FP402 FIRESEAL SILICONE

**High quality
fire resistant
silicone sealant**



FIRE PROTECT

High quality fire resistant silicone sealant



TESTED ACCORDING TO EN 1366-4
UP TO 4 HOURS OF FIRE RESISTANCE
SUITABLE FOR JOINTS UP TO 30 MM WIDE





FIRE PROTECT




FP402 FIRESEAL SILICONE

Bostik FP402 FIRESEAL SILICONE is a fire retardant, elastic, neutrally curing silicone sealant. Bostik FP402 FIRESEAL SILICONE is fire resistant for up to 4 hours in linear (movement) joints. Absorbs up to 25% of movement.

Bostik FP402 FIRESEAL SILICONE was specifically developed for fire resistant sealing of connection and expansion joints in construction and is fire resistant in case of fire. Prevents the expansion of fire, smoke or toxic gases. Fire resistance tested according to EN 1366-4 up to 180 minutes in a gap of 30mm wide. Combined with Bostik FP404 FIRE RETARDANT PU GUN FOAM up to 180 minutes in a gap of 40mm wide. Ensure that you choose the correct fire resistance for your application by consulting the classification and test reports.

 1213 22	 1213 22
Bostik B.V.	view DoP on bostik.com
DoP nr. 53001376-1501	DoP nr. 53001376-1501
EN 15651-1 F-EXT-INT-CC 25LM	EN 15651-1 F-EXT-INT-CC 25LM
EN 15651-2 G-CC 25LM	EN 15651-2 G-CC 25LM



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



BENEFITS

- Tested according to EN 1366-4
- Up to 4 hours of fire resistance
- Can be applied in joints up to 30 mm wide
- In combination with FP404 PU GUN FOAM in joints up to 40 mm wide
- Excellent processing, does not slump
- Joint movement up to 25%
- UV, water and weather resistant
- B1 fire behaviour



BOSTIK FP402 Fireseal Silicone



BOSTIK BENELUX B.V.
P: + 31 (0)162 491 000
Denariusstraat 11, 4903 RC, Oosterhout The Netherlands
E: info.benelux@bostik.com

Adhesive solutions by **ARKEMA**