



FP403 FIRESEAL HYBRID

High quality fire resistant
flexible and paintable
hybrid sealant



FIRE PROTECT

High quality fire resistant flexible and paintable hybrid sealant



TESTED ACCORDING TO EN 1366-4
UP TO 4 HOURS OF FIRE RESISTANCE
SUITABLE FOR WALL/CEILING AND WALL/FLOOR CONNECTIONS



FIRE PROTECT




FP403 FIRESEAL HYBRID

Bostik FP403 FIRESEAL HYBRID is a fire retardant, elastic and paintable hybrid sealant. Bostik FP403 FIRESEAL HYBRID is fire resistant for up to 4 hours in linear (movement) joints. Absorbs up to 25% of movement.

Bostik FP403 FIRESEAL HYBRID was specifically developed for fire resistant sealing of connection and expansion joints in construction, which in case of fire, should have a certain fire resistance and prevents spreading of fire, smoke and toxic gases. Also certified for horizontal joints, connection floor/ceiling with wall, wooden and steel. frames, stony substrates and all metal-stud applications. Fire resistance tested according to EN 1366-4 for up to 240 minutes in a joint of 30 mm wide. Choose the correct fire resistance for your application by consulting the classification and test reports.

CE 1213	UK CA 1213
18	18
Bostik B.V.	view DoP on bostik.com
DoP nr. 612887-14-7-1	DoP nr. UK612887-14-7-1
EN 15651-1 F-EXT-INT-CC 25HM	EN 15651-1 F-EXT-INT-CC 25HM
EN 15651-2 G-CC 25HM	EN 15651-2 G-CC 25HM



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur présentant un risque de toxicité par inhalation sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



BENEFITS

- Tested according to EN 1366-4
- Up to 4 hours of fire resistance
- Also suitable for wall/ceiling and wall/floor connections
- Suitable for joints up to 30 mm wide
- Certified for steel/wooden frames and metal-stud
- Excellent processing and easy toolability
- Joint movement up to 25%
- Paintable with most water based and synthetic paints
- Resistant to UV, water and weather



BOSTIK FP403 Fireseal Hybrid



BOSTIK BENELUX B.V.
P: + 31 (0)162 491 000
Denariusstraat 11, 4903 RC, Oosterhout The Netherlands
E: info.benelux@bostik.com

Adhesive solutions by **ARKEMA**