



KNOWLEDGE



EDUCATION

BETTER
RESULTS
THROUGH
KNOWLEDGE

OUR MISSION



SUPPORTED BY

Bostik P795 Explained

FACTSHEET



GLOBAL LEADER IN ADHESIVE TECHNOLOGIES

Bostik is one of the largest adhesive and sealant companies. Worldwide, we employ some 6,000 people in 50 countries across five continents. Our customers come from diverse markets, most notably the industrial manufacturing, construction and consumer sectors.

SMART INNOVATIONS

Our smart identity is underpinned by innovation. We pursue innovation vigorously, applying the latest technological advances to developing 'smart' adhesives. Today, our commitment to innovation is as strong as ever. We innovate with our customers through a global R&D network, comprising three international Smart Technology Centres and 12 regional centres. And we differentiate our business through this investment. That's why 15% of Bostik sales come from products launched in the previous three years.



Bostik P795

BOSTIK P795 SEAL'N'FLEX PREMIUM

Bostik P795 SEAL'N'FLEX PREMIUM is a New Generation one component user friendly low MDI fast curing high performance and durable polyurethane sealant. Bostik P795 SEAL'N'FLEX PREMIUM will not form bubbles during its curing process. Bostik P795 SEAL'N'FLEX PREMIUM is specifically developed as a universal sealant for sealing construction and expansion joints and joints in pedestrian walkways.

THE BASICS

The new Bostik P795 SEAL'N'FLEX PREMIUM is based upon a 'New Generation PU', meaning that Bostik will supply a **low-isocyanate** and **high performance** sealant that will not cause a **bubbling skin** during curing. In addition its technical performance is such that it doesn't need a primer, is sag-free, **label-free**, odour-free and comes with an outstanding UV-resistance and **15 month shelf life**.

PERFORMANCE WISE

Bostik P795 SEAL'N'FLEX PREMIUM is equipped with European and American certificates:

For Europe: **EN 15651 CE Marking**



- EN 15651-1: F-EXT-INT-CC 25HM
- EN 15651-4: PW-EXT-INT-CC 25HM

For America: **ASTM C920-18** Standard Specification for Elastomeric Joint Sealants:



- ASTM C920-18 (Type S, Grade NS, Class 50, Use NT & M)

Accordingly the EU regulations Bostik P795 is capable of following a joint movement of 25%, offers an elastic recovery of more than 70% and a loss of volume below 10%. Accordingly the USA regulations during Bostik P795 fulfils even a joint movement of 50%!



SUSTAINABLE WISE

Sustainable wise, Bostik P795 is a 'New Generation PU', meaning that Bostik will supply a **low-isocyanate**, is completely label (GHS and CLP) free and ticks a variety of environmental statements. No Pictograms and no risk phrase because P795 contains less than 0,1% isocyanates.


Bostik P795 comes with the **Eurofins indoor Air Comfort**®, **EMICODE EC2** and **French A+** certificates for the expels of VOC and therefor it fits within the **BREEAM** schemes for building products.



COMPARISON

Competitor

Bostik



Liability

All supplied information is the result of our tests and experience and is of general nature. However they do not imply any liability. It is the responsibility of the user to verify by his own tests if the product is suitable for the application.