



# P985 SEAL'N'FLEX SELF LEVELING

High performance  
**self leveling polyurethane  
sealant** for flooring joints



CONSTRUCTION & FACADE



# High performance **self leveling polyurethane sealant** for flooring joints



SELF LEVELING  
HIGH RESISTANCE TO CHEMICALS  
SUITABLE FOR TRAFFIC AREAS



CONSTRUCTION & FACADE




# P985 SEAL'N'FLEX SELF LEVELING



## BENEFITS

- Self-leveling, pourable
- Suitable on slope  $\leq 3\%$
- One component, ready-to-use
- Bubble-free curing
- Excellent adhesion to most construction materials
- Resistant to most chemicals and jet-fuel
- High durability, permanently elastic
- Suitable for traffic areas

CE 1213	EN 15651-4 PW-EXT- INT-CC 25HM
	DoP available on <a href="https://bostikdsds.thewerco.com/">https:// bostikdsds. thewerco.com/</a>
23	
DoP nr. 606-22-0002-1501	



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).





**BOSTIK BENELUX B.V.**  
**P: + 31 (0)162 491 000**  
Denariusstraat 11, 4903 RC, Oosterhout The Netherlands  
E: [info.benelux@bostik.com](mailto:info.benelux@bostik.com)

Adhesive solutions by **ARKEMA**