

STIX H900 RESIST+

HYBRID SOFT FLOOR ADHESIVE



TECHNICAL SOLUTIONFOR A WORRY FREE JOBSITE!

ONE COMPONENT HYBRID ADHESIVE FOR RESILIENT FLOORING IN EXTREME CONDITIONS

EASE OF APPLICATION

HIGH MECHANICAL PERFORMANCES

VERSATILE (FLOOR AND WALL)







BAY WINDOWS



- No flooring deformationExcellent resistance to temperature variation

HIGH TRAFFIC



- High mechanical resistanceIdeal for commercial applications (airports, retail, etc)

WETROOMS



- Resistant to high humidityIdeal for uniform flooring between bathroom and bedroom

WALL APPLICATION



- Non-slip designed especially for LVT Excellent initial grab

RESILIENT FLOOR COVERINGS



LVT FLOOR Requires a strong adhesive to prevent expansion or movement especially in areas that can be subject to considerable thermal changes.



RUBBER FLOOR Requires a high-performance adhesive, particularly when the rubber is thicker than 4mm.

ABSORBENT AND NON-ABSORBENT SUBFLOORS

STIX H900 RESIST+ is suitable for all kind of subfloors, especially non-absorbent backgrounds which required a strong adhesive with quick setting times.



METAL



DECOUPLING MEMBRANE

THE TIME FOR CHANGE IS NOW!

With STIX H900 RESIST+ it is now possible to securely install resilient flooring in various and/or extreme ambient conditions with a 1-component hybrid adhesive which previously had to be done with 2-component PU adhesives.

READY TO USE

EASY TO APPLY

NO MIXING

LESS WASTE

COVERAGE

vs PU 2K
(≈350g/m² vs ≈450g/m²)

SUSTAINABILITY FEATURES



VERY LOW VOC EMISSIONS

- **EC1 PLUS certified**
- A+ certified
- **BLUE ANGEL**



CARING ABOUT YOUR HEALTH

- NO SVHCs
- **NO ISOCYANATE MONOMER**
- **NO TIN CATALYST**



RECYCLED CONTENT IN PACKAGING

POST CONSUMER RECYCLED (PCR) > 35%

*Packaging with at least 35% recycled content.



ATTACHED TO YOUR WORLD

Bostik S.A.

420 Rue d'Estienne d'Orves 92700 COLOMBES - FRANCE PHONE: +33 (1) 49 00 90 00

www.bostik.com