



BOSTIK ROLL SD50

Contact Dry Adhesives



KEY BENEFITS

- Immediate grip and long-life bond.
- Ultra thin, invisible through the wall covering.
- Quick, easy and clean installation.
- Can accept immediate welding seam.
- PVC softflooring material not affected.
- High temperature resistance (-40°C à +120°C).
- Non flammable.
- Phthalate-free & solvent-free.
- Very low VOC emissions : class A+, Emission EC1 PLUS.
- Comply with LEED & BREEAM requirements.

DESCRIPTION

Thin thickness adhesive strip specially designed for use with PVC wall coverings in shower units, for hospitals, nursing homes and healthcare facilities. Replaces solvent based neoprene adhesives.

- Bonds corners (convex and concave) in PVC wall coverings.
- Bonds reduction profiles and support forms.

On wall substrates as :

- Plasterboards¹.
- Gypsum blocks¹.
- Chipboards, plywood¹, OSB¹.
- Metal or non porous substrates.

¹In case of porous surface, systematically used the dedicated primer Bostik.

PREPARATION

Ensure the subfloor is clean, sound, dry, and solid. It needs to be conformed to the regulation. Any contaminants that may hinder adhesion, such as grease, dust, some curing compounds and moisture sensitive adhesive residues must be completely removed. The porous surface needs to be prepared with the dedicated Bostik primer.

APPLICATION

Unroll and apply the tape along on the wall according the instructions uses coming from the wall covering manufacturer. Press on the entire surface of the protective paper, eliminate any air bubble and insure the adhesion everywhere. Pull protective paper and rub down the flooring or decoration.

BOSTIK ROLL SD50 is specially designed for concave and convex angles as well as the profile reduction on the bottom part of the wall.

TECHNICAL DATA

CHARACTERISTIC	
Adhesive type	Pre-coating based on synthetic resins and thin transparent weft
Colour	Translucent
Waiting time	Without, immediate use
Working time	unlimited
Application temperature	+10°C to +30°C & HR< 70%
Temperature resistance	-40°C to +120°C
Setting time	without
Consumption	1 reel = 50 meters long

STORAGE STABILITY

18 months in original package not opened between +10°C and +30°C, away from humidity

PRECAUTIONS

Protect reels from dust and moisture.

Article	Gencod	Packaging	PCB
30607859	3549212475574	48mm x 50m	5

FURTHER INFORMATION

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

SMART HELP

Please contact your local representative

