

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020

Revision date 12-May-2020 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier	
Product Name Pure substance/mixture	BOSTIK SL C510 PRO Mixture
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Recommended use Uses advised against	Hydraulic Cement, Mortar, Grout and Concrete. None known
1.3. Details of the supplier of the sa	afety data sheet
<u>Company Name</u> Bostik SA 420 rue d'Estienne d'Orves 92700 Colombes FRANCE FRANCE Tel: +33 (0)1 49 00 90 00	
E-mail address	SDS.box-EU@bostik.com
1.4. Emergency telephone number	_
United Kingdom Ireland	+44 (1785) 272650 +353 (1) 8624900 (Monday- Friday 9am-5pm)
SECTION 2: Hazards identifi	cation

2.1. Classification of the substance or mixture

Regulation ((EC)) No	1272/2008

Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)

2.2. Label Elements

Contains: Cement, portland, chemicals, Flue dust, Cement Portland



Signal word DANGER

Hazard statements

H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage.

Precautionary statements

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P261 - Avoid breathing dust.

P280 - Wear protective gloves and eye/face protection.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

P501 - Dispose of contents/ container to an approved waste disposal plant.

2.3. Other Hazards

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Quartz	238-878-4	14808-60-7	40 - <80	^		[4]
Cement, portland, chemicals	266-043-4	65997-15-1	5 - <10	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		
Quartz (fine fraction)	238-878-4	14808-60-7	0.1 - <1	STOT RE 1 (H372)		[4]
Flue dust, Cement Portland	270-659-9	68475-76-3	0.1 - <1	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		01-2119486767- 17-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.	
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.	
Eye contact	Get immediate medical advice/attention. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.	
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.	
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.	
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms	Burning sensation. Itching. Rashes. Hives.	
4.3. Indication of any immediate medical attention and special treatment needed		

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting me 5.1. Extinguishing media	asures		
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.		
5.2. Special hazards arising from the substance or mixture			
Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by skin contact.		
5.3. Advice for firefighters			
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.		

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautionsDo not get in eyes, on skin, or on clothing. Use personal protective equipment as
required. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.
Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020

Other information	Refer to protective measures listed in Sections 7 and 8.		
For emergency responders	Use personal protection recommended in Section 8.		
6.2. Environmental precautions			
Environmental precautions	Prevent further leakage or spillage if safe to do so.		
6.3. Methods and material for containment and cleaning up			
Methods for containment	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.		
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.		
6.4. Reference to other sections			
Reference to other sections	See section 8 for more information. See section 13 for more information.		

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash it before reuse.
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, inc	cluding any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up.
7.3. Specific end use(s)	
Specific Use(s) Hydraulic Cement, Mortar, Grout and	Concrete.
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Quartz	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
14808-60-7		STEL: 0.3 mg/m ³	
Limestone	-	TWA: 10 mg/m ³	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³	TWA: 4 mg/m ³
		STEL: 30 mg/m ³	STEL: 30 mg/m ³
		STEL: 12 mg/m ³	STEL: 12 mg/m ³
Cement, portland, chemicals	-	TWA: 1 mg/m ³	TWA: 10 mg/m ³
65997-15-1		STEL: 3 mg/m ³	TWA: 4 mg/m ³

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020

Revision date 12-May-2020 Revision Number 1

			STEL: 30 mg/m ³ STEL: 12 mg/m ³
Calcium sulfate 7778-18-9	-	TWA: 10 mg/m ³ STEL: 30 mg/m ³	-
Dust RR-12364-8	-	TWA: 10 mg/m³ TWA: 4 mg/m³	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³	TWA: 0.1 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Predicted No Effect Concentration No information available. (PNEC)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection	Tight sealing safety goggles.
Skin and body protection	Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Appearance Colour Odour Odour threshold	Solid Powder Grey Brown Odourless No information available	
Property	Values	Remarks • Method
pH	Not applicable .	
pH (as aqueous solution)	11.5	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	No data available	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	Cement based products react and	
	solidify in contact with water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020 Revision date 12-May-2020 Revision Number 1

Dynamic viscosity Explosive properties Oxidising properties	No data available No data available No data available	
<u>9.2. Other information</u> Solid content (%) VOC Content (%) Density	No information available No information available 1.5 g/cm ³	
SECTION 10: Stability and re	eactivity	
10.1. Reactivity		
Reactivity	No information available.	
10.2. Chemical stability		
Stability	Stable under normal conditions.	
Explosion Data Sensitivity to mechanical impact	None.	
Sensitivity to static discharge	None.	
10.3. Possibility of hazardous reactions		
Possibility of hazardous reactions	None under normal processing.	
10.4. Conditions to avoid		
Conditions to avoid	None known based on information supplied.	
10.5. Incompatible materials		
Incompatible materials	Strong acids. Strong bases. Strong oxidising agents.	
10.6. Hazardous decomposition pr	oducts	
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.	
SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Information on likely routes of exp	osure	
Product Information		
Inhalation	Based on available data, the classification criteria are not met.	
Eye contact	Causes serious eye damage.	
Skin contact	May cause irritation. May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause	

Symptoms related to the physical, chemical and toxicological characteristics

United Kingdom, Ireland - BE

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020

Symptoms

Redness. Burning. May cause blindness. Itching. Rashes. Hives.

Numerical measures of toxicity

Acute Toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	>2000 mg/kg (Rattus)		
Cement, portland, chemicals 65997-15-1	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	
Quartz (fine fraction) 14808-60-7	>2000 mg/kg (Rattus)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Causes serious eye damage.
Respiratory or skin sensitisation	May cause sensitisation by skin contact.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

12.2. Persistence and degradability

Persistence and degradability No information available.

.

12.3. Bioaccumulative potential

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020

Bioaccumulation

There is no data for this product.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Quartz	-	0
14808-60-7		

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB. .

Chemical name	PBT and vPvB assessment
Flue dust, Cement Portland	PBT assessment does not apply
68475-76-3	

12.6. Other adverse effects

Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID) 14.1 UN Number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) 14.4 Packing Group 14.5 Environmental hazards 14.6 Special Provisions	Not regulated Not regulated Not regulated Not applicable None
IMDG 14.1 UN number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) 14.4 Packing group	Not regulated Not regulated Not regulated Not regulated
14.5 Marine Pollutant14.6 Special Provisions14.7 Transport in bulk according	Np None to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1	UN number	Not regulated
14.2	Proper Shipping Name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable
14.6	Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Cement, portland, chemicals	65997-15-1	47

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

BOSTIK SL C510 PRO Supercedes Date: 12-May-2020

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H372 - Causes damage to organs through prolonged or repeated exposure

Legend

3	
TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By	Product Safety & Regulatory Affairs
Revision date	12-May-2020
Indication of changes	
Revision note	SDS sections updated: 2, 3.
Training Advice	No information available
Further information	No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet