

BOSTIK SL C910 XPRESS
Supersedes Date: 04-Nov-2019Revision date 22-Jan-2020
Revision Number 3**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier****Product Name** BOSTIK SL C910 XPRESS
Pure substance/mixture Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Cement.
Uses advised against None known.**1.3. Details of the supplier of the safety data sheet****Company Name**Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****Emergency Telephone** No information available**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)

2.2. Label Elements

Contains: Cement, portland, chemicals, Flue dust, Cement Portland

**Signal word**
DANGER**Hazard statements**H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supersedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P264 - Wash hands and face thoroughly after handling
P280 - Wear protective gloves and eye/face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards

Product dust may be irritating to eyes, skin and respiratory system
When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers
Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Quartz	238-878-4	14808-60-7	>25 - <40	^		Exempt
Cement, portland, chemicals	266-043-4	65997-15-1	10 - <20	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		No data available
Flue dust, Cement Portland	270-659-9	68475-76-3	0.1- <1	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		01-2119486767-17-XXXX
Quartz (fine fraction)	238-878-4	14808-60-7	0.1- <1	STOT RE 1 (H372)		Exempt

Full text of H- and EUH-phrases: see section 16

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supercedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Consult an ophthalmologist. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Causes serious eye damage. Inhalation of dust in high concentration may cause irritation of respiratory system. Irritating to skin.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by skin contact.
Hazardous combustion products	Carbon oxides.

5.3. Advice for firefighters

Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supersedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Avoid generation of dust.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Use personal protective equipment as required.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

7.3. Specific end use(s)

Specific Use(s)
Cement.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Quartz 14808-60-7	TWA: 0.1 mg/m ³
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m ³

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supersedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)
Quartz (14808-60-7)

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Face protection shield. Wear safety glasses with side shields (or goggles).

Hand protection For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection Suitable protective clothing. Apron. Gloves made of plastic or rubber. Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid generation of dust.

Recommended filter type: with filter for particulates.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Powder
Colour Grey
Odour No information available
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	No data available
Melting point / freezing point	Not applicable	. °C
Boiling point / boiling range	. °C	
Flash point	. °C	
Evaporation rate	Not applicable	.
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	1.4	
Water solubility	Partially soluble	Cement based products react and solidify in contact with water
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supercedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Kinematic viscosity	Not applicable . mm ² /s
Dynamic viscosity	Not applicable .
Explosive properties	No data available
Oxidising properties	No data available

9.2. Other information

Solid content (%)	100
Softening Point	Not relevant
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract.

Eye contact Causes serious eye damage.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supersedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	>2000 mg/kg (Rattus)		
Cement, portland, chemicals 65997-15-1	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	
Quartz (fine fraction) 14808-60-7	>2000 mg/kg (Rattus)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity .

12.2. Persistence and degradability

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supersedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Quartz 14808-60-7	-	0

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB. .

Chemical name	PBT and vPvB assessment
Flue dust, Cement Portland 68475-76-3	PBT assessment does not apply

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN Number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing Group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special Provisions None

IMDG

14.1 UN number Not regulated
14.2 Proper Shipping Name Not regulated

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supercedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine Pollutant Np
14.6 Special Provisions None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Cement, portland, chemicals	65997-15-1	47

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

France

Europe - BE

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supersedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Quartz 14808-60-7	RG 25
Cement, portland, chemicals 65997-15-1	RG 8, RG 10
Quartz (fine fraction) 14808-60-7	RG 25

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) WGK 1

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands
Quartz 14808-60-7	Present (respirable dust, crystalline)
Quartz (fine fraction) 14808-60-7	Present (respirable dust, crystalline)

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H372 - Causes damage to organs through prolonged or repeated exposure

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
Ceiling Maximum limit value * Skin designation
PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
STOT RE Specific target organ toxicity - Repeated exposure
STOT SE Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

SAFETY DATA SHEET

BOSTIK SL C910 XPRESS
Supersedes Date: 04-Nov-2019

Revision date 22-Jan-2020
Revision Number 3

Revision date 22-Jan-2020

Indication of changes

Revision note SDS sections updated: 1.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet