

# A725

# RAPID FINE FILLER READY MIXED FINE SURFACE FILLER

## **TECHNICAL DATA SHEET**

#### **BENEFITS**

- Ready mixed
- Ready to use
- Smooth structure
- Sandable
- Paintable
- Easy to use
- Almost odourless

## **PRODUCT DESCRIPTION**

**Bostik A725 RAPID FINE FILLER** an filler based on acrylic dispersion for interior use in filling holes, cracks and other irregularities in walls made of various materials.

## **APPLICATIONS**

**Bostik A725 RAPID FINE FILLER** was specifically developed for filling and repairing screw holes, holes, cracks and other irregularities in wall and ceiling for interior applications.

# **DIRECTIONS OF USE**

For best results, the product should be applied without pressure.



TECHNICAL DATA		
Application		+5°C to + 40°C
temperature		
Base		Acrylic dispersion
Density	ISO 1183-1	1,27 g/ml
Frost resistance		Up to - 15°C
during		
transportation		
Sandable		After 3 hours

These values are typical properties and may vary +/-3%

#### **LIMITATIONS**

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for movement joints

## **SURFACE PREPARATIONS AND FINISHING**

Application temperature + 5°C to + 40°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Substrates to be cleared of all loose particles, absorbent substrates do not need to be absolutely dry. Very porous substrates like: gypsum, aerated concrete, limestone, etc, need to be primed with a mixture of 1 part **Bostik A725 RAPID FINE FILLER** and 2 parts water. Always test adhesion prior to application. Finish and smooth with water.

#### **PAINTABILITY**

Bostik A725 RAPID FINE FILLER is paintable when fully dry. During curing product will show shrinkage, which can cause cracking of the paint. Paintable with water based and synthetic paints. Painting with highly filled emulsion paints can create cracking. We recommend testing compatibility with paint prior to application.

## **CLEANING**

Tools should be cleaned after use with water. Hands can be cleaned with **Bostik T150 CLEANING WIPES** and/or water and soap.

# COLOUR(S)

Off white

## **PACKAGING**

250 ml tubes, 12 per box

For product specifications, please refer to the Online Product Detail Page

## **SHELF LIFE**

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 12 months from production date, stored in a dry place.

## **HEALTH & SAFETY**

Product Safety Data Sheet must be read and understood before use. These are available on request and via the websites.

## **CERTIFICATIONS**

A+ French VOC Regulation

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce

# Bostik Benelux B.V.

Denariusstraat 11 · NL-4903 RC Oosterhout Tel.: +31 (0)162 491 000 www.bostik.com



Bostik Sealing & Bonding Technical Data Sheet A725 RAPID FINE FILLER-092021