

# FIX A760 TECH

## ULTRA-HIGH-PERFORMANCE TACKIFIER ADHESIVE

### KEY BENEFITS

- Allows for subsequent removal and replacement of the flooring.
- High-performance, permanent tacky film
- All types of absorbent or non absorbent subfloors



### APPLICATIONS

#### DESCRIPTION

FIX A760 TECH is a heavy-duty tackifier adhesive for application of all types of removable carpet and vinyl tiles, loose-lay LVT, heterogenous PVC flooring and broadloom carpets.

Allows for removal and recycling of carpet tiles. Multipurpose.

#### DESTINATION

Heavy-duty tackifier adhesive for application of all types of removable carpet and vinyl tiles, loose-lay LVT, heterogenous PVC flooring and broadloom carpets.

For interior use only.

#### Associated floor coverings :

- VCT : Vinyle Composition Tile
- PVC heterogeneous in tiles or sheets
- Relief Expanded Vinyles
- Crunchy tiles
- Carpets all types in sheets
- Heavy removable carpets tiles
- Laminate floors on underlay

### PRODUCT CHARACTERISTICS

<b>Colour</b>	Pink
<b>Composition</b>	Acrylic water based
<b>Storage / Shelf Life*</b>	12 months
<b>Waiting time**</b>	Normally absorbent surfaces : 45-60min Non absorbent surfaces : 2-2.5h
<b>Open time**</b>	Permanently tacky
<b>Walk on time**</b>	Immediately
<b>Coverage</b>	60-120g/m <sup>2</sup>
<b>Application temperature</b>	10 to 25°C

\*from date of manufacture in original, unopened packaging, clear of the ground, in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost, damp, condensation and dew.

\*\*these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

## DIRECTIONS FOR USE

### PREPARATION

#### Subfloor:

Ensure the subfloor is in accordance with building standards. Subfloors must be clean, sound, dry (<75%RH), and free from contaminants that may impair adhesion e.g. dust, grease, paint, plaster, polish, water softenable adhesive etc.

For subfloors that are not sufficiently smooth or require height build up to receive the particular floor covering being bonded, an application of a suitable Bostik self-levelling compound and primer system is recommended. Please consult Technical Services for advice on specific products and subfloors.

Surfaces should be thoroughly cleaned and vacuumed. Prime boards and other porous surfaces and allow to dry. This is particularly important with hardboard, chipboard and plywood.

Before applying any adhesive, ensure the substrate is dry and dust free.

It is suitable for use over existing PVC and linoleum, however, ensure all traces of polish and contaminants have been removed.

#### Underfloor heating systems:

Underfloor heating systems must be switched off for 48 hours before installation. Wait 7 days after installation before gradually turning up underfloor heating.

### APPLICATION

Apply the fixative with a 12 mm non-drip roller, or with a trowel (avoid over applying). The product covers 60 to 120g/m<sup>2</sup> depending on the type of coating and the spatula used:

Areas of applications :	Application :
Normally absorbent surfaces	100 to 120 g/m <sup>2</sup>
Wood and non-absorbent surfaces	60 to 80 g/m <sup>2</sup>

Respect a drying time of 45 minutes to 60 minutes on normally absorbent subfloors and of 2 hours to 2.5 hours on non absorbent subfloors minimum to obtain the permanent tackifying effect and to allow the subsequent removal of the sealing tiles.

NOTE: Laying into wet adhesive on metal surfaces will entrap moisture and may cause rusting.

### SUBSEQUENT REMOVAL OF THE FLOORING

The replacement of the tiles can be carried out without product. The subsequent removal of felt-backed carpets with felt backing is made easier.

During this removal, the felt backing remains attached to the textile part, only the adhesive the adhesive remaining on the backing is removed or not, depending on the type of renovation planned. It can be removed with water with detergent or alkaline detergent.

### CLEANING

Clean tools and equipment with warm water immediately after use. Remove any adhesive from the surface of the floor covering with a damp cloth.

Code	UC	PCB	PALLET.	GENCOD
30617604	2 kg	1	150	3549212487041
30615497	5 kg	1	80	3549212484781
30615496	19 kg	1	16	3549212484774

### SAFETY

For more details, consult the safety data sheet on <https://bostiksd.thevercs.com/default.aspx>

*The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the pat*

BOSTIK TECHNICAL ASSISTANCE

Smart Help +XX XX XXX XXX

