



FP 360 Putty Cord

FIRE RETARDANT PUTTY FOR DIFFICULT SERVICE PENETRATIONS

ADVANTAGES

- CE-marked
- Fire classifications up to 120 minutes
- No emissions, environmental and user friendly
- Very easy to install
- Fire sealing around services with zero or minimal annular gaps (max. 10mm)

PRODUCT

Bostik FP 360 Putty Cord is a silicon based fire rated putty, hand workable, re-usable and re-serviceable due to its non-setting properties. Bostik FP 360 Putty Cord contains a low pressure intumescent for optimal fire protection.

APPLICATIONS

Bostik FP 360 Putty Cord is designed to be easily fitted around service penetrations where the gap around the services is very small, or there is no gap at all so a conventional fire rated sealant is impossible or difficult to fit due to the required depth and backing material. The putty cords are fitted covering the gap around the services and does not need to fill the gap to the required depth. Bostik FP 360 Putty Cord will reinstate the fire rating of the partition and prevent the passage of smoke and flames in a fire, whilst also limiting sound and air movement around the service.

FEATURES

- Certified to the latest European standards EN 1366-3
- CE marked to ETAG 026-2
- Fire resistance up to 120 minutes for both integrity and insulation
- Fire sealing without any minimum annular width around services
- For cables, steel pipes, copper pipes and alupex pipes
- Gives service penetrations a high fire resistance in dry lining partitions and masonry or concrete walls and floors
- Stops penetration of both cold and hot smoke
- Self-adhesive and very easy to apply without tools
- Unaffected by moisture: can be used in wet rooms
- Never hardens and ensures a tight fit
- Can be reshaped in other sizes if necessary
- Environment- and user friendly, contains no solvents or VOC's
- Very easy to install



METHOD OF USE

Before installing PF 360 Putty cord ensure that the surfaces are clean, free from dirt, grease and other contaminants. To improve adhesion to porous substrates take a thumb size piece of Bostik FP 360 Putty Cord and gently rub over the required installation mounting area (especially important in soffit applications). Place the Bostik FP 360 Putty Cord around the services to seal the annular space as specified in the approvals or installation instructions. Press Bostik FP 360 Putty Cord into the wall and services with your thumbs to form a fillet or V-shaped joint, ensuring good contact is made between the service penetration and the wall or floor.

Before application consult the installation instructions and ETA to ensure to achieve the intended fire resistance.

LIMITATIONS

- Where Bostik FP 360 Putty Cord is to be installed against surfaces that cannot tolerate direct contact; appropriate surface preparation should be made (contact Bostik for guidance in these cases).
- For paints sensitive to sealing compounds, priming with a PVA primer is recommended.
- As Bostik FP 360 Putty Cord is silicon based, in cases where corrosion protection is a problem; some metals may require a barrier between the putty and the metal surface prior to this installation.
- Bostik FP 360 Putty Cord is not paintable

STORAGE STABILITY

Shelf life is unlimited when stored in temperatures between +5 and +30°C.

FURTHER INFORMATION

Available on request:

- Material safety data sheet
- Installation instructions FP 360 Putty Cord
- ETA 19/0388

Technical data	
Base	Silicon based putty
Technical Approval	ETAG 026-2
Density	1.55 g/ml
Colour	Red
Application temperature	+4 °C to +40 °C
Service temperature	-70 °C to +120 °C
Form	Ø15 mm x 20 cm
Packed per	5 cords per carton, total length 1m
Article number	30615327

Smart help



Bostik BV

Denariusstraat 11
4903 RC Oosterhout
T: +31 (0) 162491000
www.bostik.nl

Bostik Belux SA - NV

Meulestedekaai 86
B-900 Gent
T: +32 (0) 92551717
www.bostik.be

Bostik Ltd.

Common Road, Stafford
ST16 3EH
T: +44 (0) 1785 272625
www.bostik.co.uk

Bostik Industries Ltd.

Newton
Swords, CO. Dublin
T: +353 (1) 8624900
www.bostik.ie