

GRIP A936 XPRESS

HIGH PERFORMANCE SPECIAL PRIMER FOR NON-ABSORBENT SURFACES

KEY BENEFITS

- **Fast-drying**
- **High grip : contains quartz**
- **Easy to use : roller application**



APPLICATIONS

DESCRIPTION

GRIP A936 XPRESS is a primer for improving the adhesion of levelling compounds. GRIP A936 XPRESS adheres very well to smooth, dense and non-absorbent concrete surfaces.

DESTINATION

Bolted V 100 chipboards can be further processed after drying of GRIP A936 XPRESS at the earliest after 24 hours.

For use on absorbent substrates we recommend NIBOGRUND G 16, GRIP A500 MULTI or NIBOGRUND G 15.

Non-absorbent and standard absorbent materials :

- Ceramic tiles
- Terrazo
- Natural and artificial stone slabs
- Magnesia screed
- Poorly sanded mastic asphalt screed as well as old firmly seated floor coverings
- Homogeneous PVC
- Flexible coverings (except rubber, linoleum and old coverings with soft elastic backing)
- Old tile coverings

PRODUCT CHARACTERISTICS

Colour	Acrylate dispersion
Composition*	Red After drying : reddish-transparent
Storage / Shelf Life*	12 months
Curing time* / Floor installation	0.5 to 3 hours
Coverage	100 g/m ² /laying
Application temperature	Air: min. + 18 °C to + 23 °C; 10 to 25°C

*from date of manufacture in original, unopened packaging, clear of the ground, in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost, damp, condensation and dew.

**these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

DIRECTIONS FOR USE

PREPARATION

Subfloor:

Ensure the subfloor is in accordance with building standards. Subfloors must be clean, sound, dry (<75%RH), and free from contaminants that may impair adhesion such as dust, grease, paint, plaster, polish, water softenable adhesive, etc.

Check any remaining adhesive residues to ensure they are not water softenable, are hard, sound, and have sufficient cohesive strength to receive a primer.

Mechanically cut back any hard adhesives residues to a minimum. Remove any weak or water softenable adhesives.

Underfloor heating systems:

Underfloor heating systems must be switched off for 48 hours before installation. Wait 7 days after installation before gradually turning up underfloor heating.

APPLICATION

Apply GRIP A936 XPRESS primer using a brush or roller, ensuring that a thin even coat is obtained (coverage: approx. 80 to 120 g/m² per coat).

On porous surfaces or any surfaces likely to produce air holes in a smoothing compound, a second application will be required.

Do not over apply and avoid puddle formation.

DRYING TIMES

Allow to dry during 30 minutes to 3 hours prior to over-coating with a self-levelling compound. The curing time depends on how absorbent the subfloor is, the ambient & the floor temperature and the humidity.

Avoid using heaters that produce water vapour, such as fuel burning space heaters, as these will slow the drying rate.

CLEANING

Clean tools and equipment immediately after use with water or white spirit if the material has dried

Code	UC	PCB	GENCOD
30615690	7 kg	1	4008373130702

SAFETY

For more details, consult the safety data sheet on <https://bostiksd.thevercs.com/default.aspx>

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the pat

BOSTIK TECHNICAL ASSISTANCE

Smart Help +XX XX XXX XXX

